

Barnard

LABOR	RATE	# HOURS	TOTAL
2 Laborors	\$35	65	\$2,275

Labor Total			\$2,275
-------------	--	--	---------

EQUIPMENT			
excavator	\$120	65	\$7,800
excavator mobilization	500		\$500
2 10 wheel dump trucks	\$70	65	\$4,550
3 cy bucket loader	\$65	30	\$1,950
excavator 2	\$120	65	\$7,800

Equipment Total			\$22,600
-----------------	--	--	----------

MATERIALS	Rate	Amount	Total
4' minus rip rap 550 cu yd delivered	\$41.67	852	\$35,500
smaller chinking stone on site			\$0

Material Total			\$35,500.00
----------------	--	--	-------------

MISC.			
-------	--	--	--


Misc. Total			
-------------	--	--	--

GRAND TOTAL			\$60,375
-------------	--	--	----------

MATCH			
-------	--	--	--


+ 11,950
 72,325
 6Ae5% 3,616
 75,941

Redwood



90% of rock armor by volume must have at least 2 dimensions greater than the average dimension of any existing bed armor particles resistant to the Flood Flow

40



* * * * *

Streambed Stone Fill Design Guidance

Type	Velocity Range (fps)*	Embeddedness (in)
E1	$V \leq 9$	18
E2	$9 < V \leq 11$	24
E3	$11 < V \leq 13$	36
E4	$13 < V \leq 15$	48

*Maximum velocity should be based on a minimum 50-year design flow rate and calculated at the structure outlet.

Item xxx.xxx CY Streambed Stone Fill Specification

Type E1. The longest dimension of the stone shall be at least 18 inches, and at least 50 percent of the volume of the stone in place shall have a least dimension of 12 inches, and at least 25 percent of the particles shall have a maximum dimension of 2 inches and be well graded material.

Type E2. The longest dimension of the stone shall be at least 24 inches, and at least 50 percent of the volume of the stone in place shall have a least dimension of 18 inches, and at least 25 percent of the particles shall have a maximum dimension of 2 inches and be well graded material.

Type E3. The longest dimension of the stone shall be at least 36 inches, and at least 50 percent of the volume of the stone in place shall have a least dimension of 24 inches, and at least 25 percent of the particles shall have a maximum dimension of 2 inches and be well graded material.

Type E4. The longest dimension of the stone shall be at least 48 inches, and at least 50 percent of the volume of the stone in place shall have a least dimension of 36 inches, and at least 25 percent of the particles shall have a maximum dimension of 2 inches and be well graded material.

Notes

- The streambed stone fill shall be hard, blasted, angular rock other than serpentine rock containing the fibrous variety chrysotile (asbestos). Similar sized river sediment is an acceptable alternative as is a mixture of angular material and river sediment.
- Stone placed inside of a closed structure shall be placed such that the structure is not damaged.
- Care shall be taken to limit segregation of the materials.
- Add sand borrow item as needed to seal the bed and prevent subsurface flow.
- There shall be no subsurface flow upon final inspection.

~
USE TYPE IV STONE FILL w/ RIVER
GRAVEL TO SEAL BED

Bankfull width is 40'

Chiswick Station	Station	BS	HI	FS	Elevation
0+00	99.01	0	102.67	2.67	100.00
		13		4.83	97.16
		19		10.05	91.82
		25		11.36	91.51
		55		14.79	87.88
		76		14.74	87.93
		86		7.80	94.87


Chiswick Station




Bankfull width is 40'

Cross Section	Station	BS	HI	FS	Elevation	Note
0+50	BM 1		102.67		102.67	Nail set at 100.00' in Pine Tree base
		0		4.65	98.02	Edge of Shoulder
		12		6.66	96.01	Top of bank
		18		13.13	88.54	bottom of bank river right
		30		14.15	88.52	bankfull right bank elevation
		48		16.70	85.97	center of channel
		66		15.61	87.06	bottom of bank river left
		89		13.74	88.93	bankfull left elevation
		79		6.44	96.23	slope

Cross Section



Cross Section	Station	BS	HI	FS	Elevation	Note
1+15	BM1	0	101.58	1.58	100.00	Nail set at 100.00' in Pine Tree base
	12			4.60	96.98	Edge of Shoulder
	24			6.31	95.27	Top of bank
	29			9.89	91.69	Top of bench in bank
	36			13.86	87.72	bottom of bank river right
	56			14.49	87.09	bankfull right bank elevation
	73			15.82	85.76	center of channel
	77			15.07	86.51	bottom of bank river left
	87			13.31	88.27	bankfull left elevation
				6.26	95.32	slope



Profile

Station

Elevation

Note

Stationing

87.28 center channel
88.00 shore hole estimated at 3 feet deep no section
88.75 center channel
89.50 center channel
90.25 center channel

87.88
88.50
89.12
89.75
90.38
91.00

4
3
2
1
0

Profile

