


STATE OF NEW HAMPSHIRE
DEPARTMENT OF TRANSPORTATION
CONSTRUCTION PLANS
FEDERAL AID PROJECT


X-A004(799)
NH PROJECT NO. 42277
CHURCH STREET
OVER CONNECTICUT RIVER

DESIGN DATA

AVERAGE DAILY TRAFFIC 20_20	13000 VPD
AVERAGE DAILY TRAFFIC 20_40	16000 VPD
PERCENT OF TRUCKS	8.0%
DESIGN SPEED	30 MPH
LENGTH OF PROJECT	702 FT



LOCATION MAP
NOT TO SCALE



WALPOLE, NH - ROCKINGHAM, VT
COUNTIES OF CHESHIRE, NH AND WINDHAM, VT

SCALE: 1"=100'

PS&E
PLANS
SUBJECT TO CHANGE
DATE 6/19/2020



NHDOT THE STATE OF
NEW HAMPSHIRE
DEPARTMENT OF
TRANSPORTATION

RECOMMENDED FOR APPROVAL:

DIRECTOR OF PROJECT DEVELOPMENT

APPROVED:

ASSISTANT COMMISSIONER AND CHIEF ENGINEER DATE

FEDERAL PROJECT NO.	STATE PROJECT NO.	SHEET NO.	TOTAL SHEETS
X-A004(799)	42277	1	31

DRAWN BY	XX
CHECKED BY	XX
DATE	XX
DATE	XX

INDEX OF SHEETS	
SHEET NO.	DESCRIPTION
1	TITLE SHEET
2	INDEX OF SHEETS & GENERAL NOTES
3-4	STANDARD SYMBOLS 1-2
5	PAVEMENT MATCH AND CURB DETAILS
BRIDGE PLANS	
6	GENERAL PLAN AND ELEVATION
7	PROJECT NOTES
8	SUMMARY OF QUANTITIES
9-10	DECK PHASING 1-2
11	ABUTMENT B - STUBWALL SECTIONS
12-14	ABUTMENT B - STUBWALL PHASING 1-3
15-16	ABUTMENT B - STUBWALL REINFORCEMENT 1-2
17	DECK REINFORCING - PIER 1
18-20	FINGER JOINT EXPANSION JOINT DETAILS 1-3
21	STRIP SEAL EXPANSION JOINT
22	SIDEWALK PLATE DETAILS
23	REINFORCING SCHEDULE
24	ALUMINUM BRIDGE RAIL (3-BAR)
TRAFFIC CONTROL PLANS	
25-26	TRAFFIC CONTROL 1-2
27	TEMPORARY SIGNAL PLAN
28-29	SIGN TEXT LAYOUT 1-2
30-31	DETOUR PLAN 1-2

GENERAL NOTES

- 1

FOR STANDARD PLANS, SEE DEPARTMENT OF TRANSPORTATION WEBSITE AT: WWW.NH.GOV/DOT/ORG/PROJECTDEVELOPMENT/HIGHWAYDESIGN/STANDARDPLANS/INDEX.HTM.
- 2

HIGH TENSION OVERHEAD TRANSMISSION LINES ARE LOCATED THROUGHOUT THE PROJECT WITH CROSSINGS AT VARIOUS LOCATIONS AND RUNNING ALONG THE ROAD THROUGHOUT THE PROJECT EVEN ON REGULAR POLES. THE CONTRACTOR IS ADVISED THAT EXTREME CAUTION WILL BE REQUIRED IN THE OPERATION OF EQUIPMENT, ESPECIALLY CRANES AND PILE DRIVING EQUIPMENT.
- 3

MODIFY SUPERELEVATION ON EXISTING CURVES BY THE USE OF A LEVELING COURSE TO THE RATES INDICATED ON THE PLANS OR AS ORDERED.
- 4

EXISTING DELINEATORS AND WITNESS MARKERS THAT ARE REMOVED AND DETERMINED BY THE ENGINEER TO BE IN ACCEPTABLE CONDITION SHALL BE RESET (SUBSIDIARY). ADDITIONAL DELINEATORS AND WITNESS MARKERS ORDERED WILL BE PAID UNDER THE APPROPRIATE ITEMS OF THE CONTRACT.
- 5

NO EXISTING MONUMENTS, BOUNDS, OR BENCHMARKS SHALL BE DISTURBED WITHOUT FIRST MAKING PROVISIONS FOR RELOCATION.
- 6

PERFORM ALL WORK WITHIN THE EXISTING RIGHT-OF-WAY, UNLESS OTHERWISE SHOWN ON THE PLANS OR AS ORDERED BY THE ENGINEER.
- 7

REMOVE UNPROTECTED PROJECT MARKERS (SUBSIDIARY).
- 8

SURVEY DATA FOR THIS PROJECT WAS COLLECTED BY SDR AND THE FIELD NOTES CAN BE FOUND IN THE FIELD BOOK(S) _____. COORDINATES ARE NEW HAMPSHIRE STATE PLANE COORDINATES OF NAD83, ____ ADJUSTMENT AND THE BEARINGS ARE GRID. ELEVATIONS ARE REFERENCED TO ____ -_____.
- 9


QUANTITIES FOR EMBANKMENT AND EXCAVATION FOR SLOPE ROUNDINGS AS SHOWN ON THE TYPICALS HAVE NOT BEEN CALCULATED AND ARE NOT INCLUDED IN THE QUANTITY SUMMARIES, AND ARE CONSIDERED SUBSIDIARY TO THE APPROPRIATE 203 ITEMS.

THE FOLLOWING GENERAL NOTES WILL BE USED ON THIS PROJECT:											
1	2			5	6						






STATE OF NEW HAMPSHIRE				
DEPARTMENT OF TRANSPORTATION • BUREAU OF HIGHWAY DESIGN				
INDEX OF SHEETS & GENERAL NOTES				
REVISION DATE	DGN	STATE PROJECT NO.	SHEET NO.	TOTAL SHEETS
9-1-2016	02_Index	42277	2	31



DRAINAGE




BOUNDARIES / RIGHT-OF-WAY




UNDERGROUND UTILITIES




UTILITIES



TRAFFIC SIGNALS / ITS



CONSTRUCTION NOTES




REVISION DATE	DGN	STATE PROJECT NO.	SHEET NO.	TOTAL SHEETS
9-1-2016	04_Symb2	42277	4	31

STATE OF NEW HAMPSHIRE

DEPARTMENT OF TRANSPORTATION • BUREAU OF HIGHWAY DESIGN


STANDARD SYMBOLS 2



PAVEMENT MATCH DETAIL


SCALE: 3/4" = 1'-0"

* PROPOSED FINISHED GRADE IS 3/8"± ABOVE EXISTING GRADE




ASPHALTIC PLUG FOR CRACK CONTROL
(ABUTMENT A)

SCALE: 3/4" = 1'-0"



PROPOSED CONCRETE CURB

SCALE: 1" = 1'-0"





CURB DETAIL

SCALE: 1 1/2" = 1'-0"



STATE OF NEW HAMPSHIRE			
DEPARTMENT OF TRANSPORTATION • BUREAU OF HIGHWAY DESIGN			
PAVEMENT MATCH AND CURB DETAILS			
DGN	STATE PROJECT NO.	SHEET NO.	TOTAL SHEETS
42277curb_pave det	42277	5	31



ELEVATION
SCALE: 1"= 30'

NOTE:
FOR INDEX OF SHEETS, SEE SHEET 2.

STATE OF NEW HAMPSHIRE									
DEPARTMENT OF TRANSPORTATION * BUREAU OF BRIDGE DESIGN									
TOWN	WALPOLE, NH - ROCKINGHAM, VT				BRIDGE NO.	058/043		STATE PROJECT	42277
LOCATION	CHURCH STREET OVER CONNECTICUT RIVER								
GENERAL PLAN AND ELEVATION									BRIDGE SHEET
REVISIONS AFTER PROPOSAL				BY	DATE	BY		DATE	1 OF 19
				DESIGNED	JDG	04/2020	CHECKED	GAB	05/2020
				DRAWN	LRB	09/2019	CHECKED	JDG	05/2020
				QUANTITIES	JDG	11/2019	CHECKED	SRW	05/2020
				ISSUE DATE	FEDERAL PROJECT NO.			SHEET NO.	TOTAL SHEETS
				REV. DATE	X-A004(799)			6	31



SUBDIRECTORY	DGN LOCATOR	SHEET SCALE
BRC	42277pregen	AS NOTED

SCOPE OF WORK

- BR. NO. 058/043 CHURCH STREET OVER CONNECTICUT RIVER
- REMOVE AND REPLACE DECK PAVEMENT AND MEMBRANE
- PARTIAL AND FULL DEPTH CONCRETE DECK REPAIRS
- PARTIALLY REMOVE AND REPLACE TOPS OF ABUTMENT BACKWALLS
- INSTALL STRIP SEAL EXPANSION JOINT AT ABUTMENT B
- REMOVE MODULAR EXPANSION JOINT AT PIER 1 AND REPLACE WITH A FINGER JOINT
- RESET BRIDGE APPROACH GRANITE CURB
- REPLACE MISSING BOLTS IN DIAPHRAGM
- REMOVE EXISTING LIGHT POLES

MATERIALS AND SPECIFICATIONS

- (1) SPECIFICATIONS: AASHTO BRIDGE CONSTRUCTION SPECIFICATION WITH INTERIMS 2017
NHDOT 2016 STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION, AS AMENDED
WELDING PER AASHTO/AWS D1.5-10 WITH REVISIONS PUBLISHED BY AASHTO AS OF THE BID
OPENING DATE.
- (2) REINFORCING STEEL: AASHTO M31 (ASTM A 615) GRADE 60 EPOXY COATED
- (3) CONCRETE: PARTIAL DEPTH DECK REPAIRS = 4000 PSI
ITEM 520.01, CONCRETE CLASS AA
- FULL DEPTH DECK REPAIRS, CURB SEATS, ABUTMENT AND WINGWALL REPAIRS.
= 4,000 PSI
ITEM 520.0201, CONCRETE CLASS AA, ABOVE FOOTINGS
- BACKWALL AND DECK RECONSTRUCTION = 4,000 PSI
ITEM 520.02, CONCRETE CLASS AA, ABOVE FOOTINGS (F)

BENCHMARK NOTE

ALL EXISTING DISCS REPRESENTING STATE BENCHMARKS OR SURVEY TRIANGULATION POINTS MUST NOT BE DISTURBED. WHEN THE PROPOSED WORK INVOLVES DISTURBING ONE OF THESE DISCS, THE CONTRACTOR SHALL NOTIFY THE CONTRACT ADMINISTRATOR SUFFICIENTLY IN ADVANCE OF THE WORK TO PERMIT THE STATE TO TEMPORARILY RELOCATE THE AFFECTED MARKER.

TO THE CONTRACTOR

THE CONTRACTOR SHOULD BE AWARE THAT EXISTING STRUCTURE DIMENSIONS AND ELEVATIONS SHOWN ON THESE PLANS WERE TAKEN FROM ORIGINAL BRIDGE PLANS AND DO NOT NECESSARILY REPRESENT "AS-BUILT" DIMENSIONS AND ELEVATIONS. THE CONTRACTOR SHALL FIELD VERIFY ALL DIMENSIONS AND ELEVATIONS OF THE EXISTING STRUCTURES AND BE PREPARED TO MAKE ANY ADJUSTMENTS REQUIRED TO PROPERLY REHABILITATE THE BRIDGE. ANY DISCREPANCIES IN DIMENSIONS, CHARACTER, OR EXTENT OF THE EXISTING FEATURES SHALL BE BROUGHT TO THE ATTENTION OF THE ENGINEER PRIOR TO ADVANCING THE WORK. THE EXISTING PLANS ARE AVAILABLE ON-LINE IN THE BID PACKAGE ON THE INVITATION TO BID WEB PAGE. AFTER THE CONTRACT IS AWARDED, A COMPLETE SET OF EXISTING PLANS WILL BE FORWARDED TO THE CONTRACTOR UPON REQUEST. THE FILE NUMBER FOR THIS BRIDGE IS 2-13-1-1.

REMOVAL NOTES

- (1) REMOVAL OF EXISTING BRIDGE STRUCTURE, ITEM 502., EXCEPT AS OTHERWISE SHOWN ON THE PLANS SHALL INCLUDE REMOVAL OF THE EXISTING BRIDGE DECK, BRIDGE CURB, AND BACKWALL NEEDED FOR EXPANSION JOINT REPLACEMENT.
- (2) THE CONTRACTOR SHALL SUBMIT, FOR DOCUMENTATION IN ACCORDANCE WITH SECTION 105.02, A DETAILED OUTLINE OR PLAN OF THE PROPOSED METHOD FOR ITEM 502, PRIOR TO COMMENCEMENT OF ANY REMOVAL OF WORK.
- (3) THE EXISTING PAVEMENT AND MEMBRANE, SHALL BE REMOVED UNDER ITEM 511.0001, CONCRETE BRIDGE DECK PAVEMENT REMOVAL (F).

GENERAL CONSTRUCTION NOTES

- (1) TRAFFIC CHANNELIZING DEVICES, AND TRAFFIC CONTROL MEASURES SHALL BE IN PLACE BEFORE OPERATIONS BEGIN FOR EACH CONSTRUCTION PHASE.
- (2) THE CONTRACTOR SHALL TAKE ALL NECESSARY MEASURES TO INSURE THAT DEBRIS DOES NOT FALL INTO THE WATERWAY OR ONTO THE RAILROAD TRACKS BELOW EXISTING STRUCTURE. ALL COSTS SHALL BE PAID UNDER ITEM 502, AND SHALL INCLUDE THE ERECTION, MAINTENANCE, AND REMOVAL OF TEMPORARY STRUCTURES OR OTHER SUCH METHODS AS APPROVED.
- (3) NO SCAFFOLDS SHALL BE ERECTED OR OPERATIONS CONDUCTED IN THE ROADWAY, UNLESS APPROVED BY THE CONTRACT ADMINISTRATOR.
- (4) THE WELDING OF ATTACHMENTS TO STRUCTURAL STEEL FOR CONSTRUCTION PURPOSES SHALL NOT BE PERMITTED UNLESS APPROVED BY THE NHDOT, BUREAU OF BRIDGE DESIGN.
- (5) PRIOR TO BEGINNING CONSTRUCTION, THE CONTRACTOR SHALL MAKE A RECORD OF THE EXISTING PAINT PAVEMENT MARKINGS. UPON COMPLETION OF THE BRIDGE WORK, THE PAVEMENT MARKINGS SHALL BE REPLACED IN KIND WITH ITEM 632.0104, RETROREFLECTIVE PAINT PAVE, MARKING, 4" LINE.

GENERAL CONSTRUCTION NOTES (CONT)

- (6) ALL EXPOSED EDGES OF CONCRETE SHALL BE CHAMFERED 3/4", UNLESS OTHERWISE NOTED.
- (7) ITEM 538.6, BARRIER MEMBRANE, HEAT WELDED - MACHINE METHOD (F) SHALL BE OVERLAPPED PER MANUFACTURER'S REQUIREMENTS. AT DECK ENDS AND CURB LINES, A SEALANT/REPAIR MASTIC COMPATIBLE WITH ITEM 538.6 SHALL BE PLACED BETWEEN THE NEW MEMBRANE AND THE END DECK OR CURB TO SEAL THE MEMBRANE. ALL COSTS SHALL BE SUBSIDIARY TO ITEM 538.6.
- (8) REMOVE ANY EXISTING LOOSE OR FLAKING EPOXY COATING FROM THE BACKWALL AND SEATS AS DIRECTED. COSTS PAID UNDER ITEM 502.
- (9) FOR SALVAGE OF MATERIALS SEE PROSECUTION OF WORK.
- (10) ITEM 538.2, BARRIER MEMBRANE, PEEL AND STICK - VERTICAL SURFACES (F). 2' WIDE, SHALL BE PLACED CENTERED OVER ALL HORIZONTAL AND VERTICAL CONSTRUCTION JOINTS WITH PROTECTION BOARD (SUBSIDIARY) EXCEPT THAT BARRIER SHALL COVER THE ENTIRE VERTICAL SURFACE OF THE BACK OF BACKWALL TO 1'-0" ONTO THE EXISTING APPROACH SLAB AS SHOWN IN SECTION A-A RECONSTRUCTION SHOWN ON BRIDGE SHEET 6.
- (11) SUPPORT OF EXCAVATION NECESSARY TO COMPLETE WORK SHALL BE SUBSIDIARY TO THE EXCAVATION ITEMS OF WORK.
- (12) APPLY PAVEMENT JOINT ADHESIVE ALONG ALL LONGITUDINAL JOINTS BETWEEN PAVEMENT PASSES AND ALONG BRIDGE CURB LINES AND EXPANSION JOINT ARMORING PRIOR TO PLACING ALL PAVEMENT COURSES. FOR BRIDGE BASE COURSE APPLY ITEM 403.61, PAVEMENT JOINT ADHESIVE (BRIDGE BASE) AND FOR WEARING COURSE APPLY ITEM 403.6, PAVEMENT JOINT ADHESIVE - ROADWAY ITEM.
- (13) ITEM 563.8, RESETTING BRIDGE RAIL, SHALL BE PAID AS 1 LF PER POST.

REINFORCING NOTES

- (1) EXISTING REINFORCING STEEL, UNLESS OTHERWISE SHOWN/NOTED IN THE PLANS, SHALL BE RETAINED.
- (2) EXISTING REINFORCING STEEL THAT IS TO REMAIN IN PLACE WITHIN THE REMOVAL AREAS SHALL BE CUT AS REQUIRED TO PROVIDE 2 1/2" MINIMUM CLEAR COVER FROM THE PROPOSED CONCRETE SURFACES, EXCEPT AS OTHERWISE NOTED. ALL COSTS INCLUDED IN ITEM 502. ALL NEW REINFORCING BARS SHALL HAVE A MINIMUM CLEAR COVER OF 2 1/2" FROM PROPOSED CONCRETE SURFACES.
- (3) ALL REINFORCING TO REMAIN IN PLACE SHALL BE INSPECTED FOR DAMAGE OR CORROSION JOINTLY BY THE CONTRACT ADMINISTRATOR AND CONTRACTOR AFTER EACH REMOVAL PHASE. ALL NEW REINFORCING STEEL REQUIRED TO REPAIR OR REPLACE EXISTING REINFORCEMENT SHALL BE PAID UNDER ITEM 1002.1, REPAIRS OR REPLACEMENTS AS NEEDED - BRIDGE STRUCTURES.
- (4) PLACE REINFORCING STEEL TO AVOID RAIL POST ANCHOR ASSEMBLIES AND ANCHOR BOLTS AND EXPANSION JOINT ASSEMBLIES.
- (5) REINFORCING LEGEND: SP = SPACE, SPL = SPLICE, FS = FAR SIDE.
NS = NEAR SIDE, BOT = BOTTOM, ALT = ALTERNATING
- (6) FOR TYPICAL BEND DETAILS, RECOMMENDED PIN DIAMETER "D" OF BENDS AND HOOKS AND OTHER STANDARD PRACTICE SEE CURRENT CONCRETE REINFORCING STEEL INSTITUTE "MANUAL OF STANDARD PRACTICE".
- (7) PROPOSED REINFORCEMENT, AS SHOWN IN THE PLANS, REPLACING EXISTING REBAR TO BE REMOVED, SHALL BE PAID UNDER ITEM 544.2, REINFORCING STEEL EPOXY COATED (F) AND ITEM 544.21, REINFORCING STEEL, EPOXY COATED, MECHANICAL CONNECTORS (F).
- (8) GALVANIC CORROSION PROTECTION SYSTEMS, ITEMS 540.511 AND 540.512, SHALL BE PLACED IN THE DECK AS SHOWN ON THE PLANS. SEE SPECIAL PROVISION FOR ADDITIONAL INFORMATION.

SUPERSTRUCTURE REHABILITATION NOTES

- (1) BOLTS ARE MISSING AT THE LATERAL CONNECTION BRACKET (2 BOLTS). NEW 7/8" DIAMETER BOLTS CONFORMING TO THE REQUIREMENTS OF ITEM 550 SHALL FILL THESE HOLES. ALL COSTS SHALL BE PAID UNDER ITEM 1002.1. REPAIRS OR REPLACEMENTS AS NEEDED - BRIDGE STRUCTURES. NO OTHER STRUCTURAL REPAIRS ARE ANTICIPATED.
- (2) ITEM 538.6, BARRIER MEMBRANE, HEAT WELDED, MACHINE METHOD (F) SHALL BE LAPPED PER MANUFACTURER'S REQUIREMENTS. AT DECK ENDS, WHERE THE MEMBRANE WILL NOT LAP NEW OR EXISTING MEMBRANE, A SEALANT/REPAIR MASTIC COMPATIBLE WITH ITEM 538.6 SHALL BRIDGE ANY GAP BETWEEN THE EXISTING AND NEW MEMBRANE, OR BETWEEN THE NEW MEMBRANE AND THE END OF DECK WHEN THERE IS NO EXISTING MEMBRANE. ALL COSTS SHALL BE SUBSIDIARY TO ITEM 538.6.
- (3) DURING ALL REMOVAL AND REPAIR OPERATIONS EXTREME CARE SHALL BE TAKEN NOT TO DAMAGE EXISTING DECK REINFORCEMENT. ANY DAMAGE SHALL BE IMMEDIATELY REPORTED TO THE BUREAU OF BRIDGE DESIGN AND REPAIRED AS DIRECTED, AT THE CONTRACTOR'S EXPENSE.
- (4) DURING CONCRETE END OF DECK REMOVAL OPERATIONS, EXTREME CARE SHALL BE TAKEN NOT TO DAMAGE TOP FLANGES OF EXISTING GIRDERS. ANY DAMAGE SHALL BE IMMEDIATELY REPORTED TO THE BUREAU OF BRIDGE DESIGN AND REPAIRED AS DIRECTED, AT THE CONTRACTOR'S EXPENSE.
- (5) TO ACCOMPLISH THE PROPOSED EXPANSION JOINT REPAIRS, THE EXISTING DECK SHALL BE REMOVED TO LIMITS SHOWN IN THE PLANS UNDER ITEM 502.. REMOVAL OF EXISTING BRIDGE STRUCTURE. ALL EXPOSED CONCRETE SURFACES OF THE DECK SHALL BE SAWCUT 1" DEEP TO PROVIDE CLEAN REMOVAL LINES (ALL COSTS INCLUDED IN ITEM 502.). NEW DECK END SHALL BE RECONSTRUCTED WITH ITEM 520.0201. PRIOR TO PLACING NEW CONCRETE, THE REMOVAL SURFACES SHALL BE BLAST CLEANED AND SATURATED SURFACE DRY (ALL COSTS INCLUDED IN ITEM 520.0201).
- (6) AFTER REMOVAL OF EXISTING PAVEMENT AND MEMBRANE, THE EXISTING CONCRETE BRIDGE DECK SHALL BE "SOUNDED" TO DETERMINE AREAS REQUIRING PARTIAL AND FULL DEPTH DECK REPAIRS. ALL COSTS TO BE INCLUDED IN ITEM 511.02 OR ITEM 511.03.
- (7) DETERIORATED AREAS OF DECK SHALL BE PATCHED WITH CONCRETE CLASS AA. PRIOR TO PLACING NEW CONCRETE, THE PREPARED AREAS SHALL BE BLAST CLEANED AND SATURATED SURFACE DRY (ALL COSTS SUBSIDIARY TO ITEM 520.01 OR 520.0201).
- (8) UNLESS OTHERWISE NOTED, HOLES DRILLED INTO EXISTING CONCRETE SHALL BE DRILLED 1/2" DIAMETER LARGER THAN THE BAR DIAMETER AND GROUTED WITH AN APPROVED HIGH STRENGTH, NON-SHRINK CEMENTITIOUS GROUT. ALL COSTS FOR DRILLING AND GROUTING SHALL BE PAID FOR UNDER ITEM 520.0201.
- (10) FOR DECK PATCHING, CURB OR BACKWALL WORK, ALL NEW REINFORCEMENT SHALL BE EPOXY COATED BARS. THE EXISTING BLACK REINFORCEMENT SHALL BE COATED WITH ANTI-CORROSION COATING AS NOTED IN THE SUPPLEMENTAL SPECIFICATION AMENDMENT TO SECTION 511. ALL COSTS SHALL BE SUBSIDIARY TO ITEM 511.0x, PREPARATION FOR PARTIAL/FULL DEPTH CONCRETE BRIDGE DECK REPAIRS.
- (11) EXPOSED SURFACES OF EXISTING ABUTMENTS, WINGS, BACKWALLS, AND BRIDGE SEATS SHALL BE WASHED, SUBSIDIARY TO ITEM 534.3, IN SUCH A MANNER THAT OVERSPRAY INTO SURFACE WATERS IS KEPT TO A MINIMUM. IF THE WATER BEADS, NO COATING NEEDS TO BE APPLIED. IF THE WATER DOES NOT BEAD COAT THE SURFACE WITH ITEM 534.3, WATER REPELLENT (SILANE-SILOXANE), APPLICATION RATE = 150 SF/GAL
- (12) RESET GRANITE APPROACH CURB AS SHOWN ON THE PLANS, ITEM 609.5.

</

QUANTITIES

ITEM NO.	ITEM DESCRIPTION	UNIT	VT	QUANTITY	NH	TOTAL
				QUANTITY	QUANTITY	QUANTITY
304.301	CRUSHED GRAVEL	CY	---	20	20	20
403.119	HOT BITUMINOUS PAVEMENT, MACHINE METHOD, HIGH STRENGTH	T	275	310	585	
403.12	HOT BITUMINOUS PAVEMENT, HAND METHOD	T	---	2	2	
403.6	PAVEMENT JOINT ADHESIVE	LF	623	1772	2395	
403.61	PAVEMENT JOINT ADHESIVE (BRIDGE BASE)	LF	712	2026	2738	
403.911	HOT BITUMINOUS BRIDGE PAVEMENT, 1" BASE COURSE	T	42	119	161	
403.99	TEMPORARY BITUMINOUS PAVEMENT	T	5	5	10	
410.22	ASPHALT EMULSION FOR TACK COAT	GAL	240	275	515	
417	COLD PLANING BITUMINOUS SURFACES	SY	248	149	397	
502	REMOVAL OF EXISTING BRIDGE STRUCTURE	U	0.26	0.74	1	
504.1	COMMON BRIDGE EXCAVATION (F)	CY	---	30	30	
511.0001	CONCRETE BRIDGE DECK PAVEMENT REMOVAL (F)	SY	731	2080	2811	
511.02	PREPARATION FOR PARTIAL DEPTH CONCRETE BRIDGE DECK REPAIRS	SY	166	474	640	
511.03	PREPARATION FOR FULL DEPTH CONCRETE BRIDGE DECK REPAIRS	SY	31	89	120	
512.02	PREPARATION FOR CONCRETE REPAIRS, CLASS II	SY	1	4	5	
520.01	CONCRETE CLASS AA	CY	19	55	74	
520.02	CONCRETE CLASS AA ABOVE FOOTINGS (F)	CY	18	21	39	
520.0201	CONCRETE CLASS AA ABOVE FOOTINGS	CY	10	27	37	
534.3	WATER REPELLENT (SILANE-SILOXANE)	GAL	30	66	96	
538.2	BARRIER MEMBRANE, PEEL AND STICK - VERTICAL SURFACES (F)	SY	---	13	13	
538.6	BARRIER MEMBRANE, HEAT WELDED - MACHINE METHOD (F)	SY	731	2081	2812	
540.511	GALVANIC CORROSION PROTECTION SYSTEM (DISTRIBUTED ANODES)	LF	49	141	190	
540.512	GALVANIC CORROSION PROTECTION SYSTEM (DISCRETE ANODES)	EA	741	2109	2850	
541.5	PVC WATERSTOPS, NH TYPE 5 (F)	LF	---	49	49	
544.2	REINFORCING STEEL, EPOXY COATED (F)	LB	1804	4013	5817	
544.21	REINFORCING STEEL, EPOXY COATED, MECHANICAL CONNECTORS (F)	LB	402	624	1026	
559.41	ASPHALTIC PLUG FOR CRACK CONTROL (F)	LF	13	36	49	
561.1001	PREFABRICATED STRIP SEAL EXPANSION JOINT (F)	LF	13	36	49	
561.3001	PREFABRICATED FINGER EXPANSION JOINT (F)	LF	13	36	49	
562.1	SILICONE JOINT SEALANT (F)	LF	97	107	204	
563.073	ALUMINUM POST ASSEMBLY FOR F RAIL (3-BAR)	EA	4	2	6	
563.8	RESETTING BRIDGE RAIL	LF	4	2	6	
565.802	ADJUSTING BRIDGE APPROACH RAIL	U	---	2	2	



QUANTITIES (CONTINUED)

			VT	NH	TOTAL
609.5	RESET GRANITE CURB	LF	116	60	176
616.171	PORTABLE TRAFFIC SIGNAL SYSTEM	EACH	3	---	3
616.191	ALTERATIONS TO TRAFFIC SIGNALS	EACH	---	1	1
618.61	UNIFORMED OFFICER WITH VEHICLE	\$	0.26	0.74	1
618.7	FLAGGERS	HR	208	592	800
619.1	MAINTENANCE OF TRAFFIC	U	0.26	0.74	1
619.25	PORTABLE CHANGEABLE MESSAGE SIGN	U	1	3	4
628.2	SAWED BITUMINOUS PAVEMENT	LF	141	45	186
628.22	SAWED BITUMINOUS PAVEMENT (BRIDGE)	LF	308	976	1284
632.0104	RETROREFLECTIVE PAINT PAVE. MARKING, 4" LINE	LF	735	2607	3342
632.0124	RETROREFLECTIVE PAINT PAVE. MARKING, 24" LINE	LF	20	12	32
632.0118	RETROREFLECTIVE PAINT PAVE. MARKING, 18" LINE	LF	14	38	52
632.02	RETROREFLECTIVE PAINT PAVE. MARKING, SYMBOL OR WORD	SF	---	12	12
632.911	OBLITERATE PAVEMENT MARKING LINE, 12" WIDE & UNDER	LF	75	215	290
692	MOBILIZATION	U	0.26	0.74	1
698.12	FIELD OFFICE TYPE B	MON	2	6	8
1002.1	REPAIRS OR REPLACEMENTS AS NEEDED - BRIDGE STRUCTURES	\$	0.26	0.74	1
1010.15	FUEL ADJUSTMENT	\$	0.26	0.74	1
1010.41	QUALITY CONTROL / QUALITY ASSURANCE (QC/QA) FOR CONCRETE	\$	0.26	0.74	1




SUBDIRECTORY	.DGN LOCATOR	SHEET SCALE
BRC	02a_Quantities	AS NOTED

STATE OF NEW HAMPSHIRE									
DEPARTMENT OF TRANSPORTATION * BUREAU OF BRIDGE DESIGN									
TOWN	WALPOLE, NH - ROCKINGHAM, VT			BRIDGE NO.	058/043		STATE PROJECT	42277	
LOCATION CHURCH STREET OVER CONNECTICUT RIVER									
SUMMARY OF QUANTITIES									BRIDGE SHEET
REVISIONS AFTER PROPOSAL			BY	DATE	CHECKED	BY	DATE	3 OF 19	
			DESIGNED	JDG	05/2020	CHECKED	SRW	05/2020	FILE NUMBER
			DRAWN			CHECKED			
			QUANTITIES			CHECKED			
			ISSUE DATE		FEDERAL PROJECT NO.			SHEET NO.	TOTAL SHEETS
			REV. DATE		X-A004(799)			8	31




- ## PHASE 1
1. REMOVE NORTHERN GRANITE CURB AND PLACE TEMPORARY PAVEMENT
 2. INSTALL TRAFFIC CONTROL AND DIVERT ROADWAY AND PEDESTRIAN TRAFFIC TO TEMPORARY LOCATIONS. DETOUR TRUCK TRAFFIC
 3. THE TEMPORARY SIDEWALK SHALL MEET ADA REQUIREMENTS
 4. A TEMPORARY WOODEN BRIDGE OR STEEL PLATE MAY BE UTILIZED OVER THE PEDESTRIAN FACILITIES TO AVOID A FIELD SPLIT
 5. ANY OPEN AREAS IN THE WORKZONE SHALL BE PLATED WHEN THE CONTRACTOR IS NOT PRESENT
 6. COMPLETE AND OPEN SIDEWALK BEFORE PAVING AND MEMBRANE OPERATIONS BEGIN



- PHASE 2
1. MAINTAIN WESTBOUND TRAFFIC IN NORTHERN TEMPORARY LANE.
 2. SHIFT EASTBOUND TRAFFIC TO SOUTHERN TEMPORARY LANE.
 3. MAINTAIN PEDESTRIAN TRAFFIC ON SIDEWALK.
 4. MAINTAIN TRUCK DETOUR.


STATE OF NEW HAMPSHIRE									
DEPARTMENT OF TRANSPORTATION * BUREAU OF BRIDGE DESIGN									
TOWN WALPOLE, NH - ROCKINGHAM, VT			BRIDGE NO. 058/043			STATE PROJECT 42277			
LOCATION CHURCH STREET OVER CONNECTICUT RIVER									
DECK PHASING 1									BRIDGE SHEET
REVISIONS AFTER PROPOSAL			BY		DATE		BY		DATE
			DESIGNED	ISM	04/2019	CHECKED	JDG	05/2020	4 OF 19
			DRAWN	JTB	05/2020	CHECKED	JDG	05/2020	FILE NUMBER
			QUANTITIES	JDG	05/2020	CHECKED	SRW	05/2020	
			ISSUE DATE		FEDERAL PROJECT NO.			SHEET NO.	
			REV. DATE		X-A004(799)			9	
								TOTAL SHEETS	
								31	

SUBDIRECTORY	.DGN LOCATOR	SHEET SCALE
HWY	42277typ	AS NOTED



PHASE 3 CONSTRUCTION

SCALE: 3/8"=1'-0"



DISCRETE GALVANIC PROTECTION DETAIL

NOT TO SCALE


PHASE 3

1. SHIFT WESTBOUND TRAFFIC TO CENTER TEMPORARY LANE.
2. MAINTAIN EASTBOUND TRAFFIC IN TEMPORARY LANE.
3. MAINTAIN PEDESTRIAN TRAFFIC ON SIDEWALK.
4. MAINTAIN TRUCK DETOUR.




SUBDIRECTORY	.DGN LOCATOR	SHEET SCALE
HWY	42277typ	AS NOTED

STATE OF NEW HAMPSHIRE									
DEPARTMENT OF TRANSPORTATION * BUREAU OF BRIDGE DESIGN									
TOWN	WALPOLE, NH - ROCKINGHAM, VT			BRIDGE NO.	058/043		STATE PROJECT	42277	
LOCATION CHURCH STREET OVER CONNECTICUT RIVER									
DECK PHASING 2								BRIDGE SHEET	
REVISIONS AFTER PROPOSAL				BY	DATE		BY	DATE	5 OF 19
				DESIGNED	ISM	04/2019	CHECKED	JDG	05/2020
				DRAWN	JTB	05/2020	CHECKED	JDG	05/2020
				QUANTITIES	JDG	05/2020	CHECKED	SRW	05/2020
				ISSUE DATE		FEDERAL PROJECT NO.		SHEET NO.	TOTAL SHEETS
				REV. DATE		X-A004(799)		10	31



SECTION A-A REMOVAL
SCALE: 3/4" = 1'-0"



SECTION A-A RECONSTRUCTION
SCALE: 3/4" = 1'-0"



NOTE:

- FOR LOCATION OF SECTION A-A REMOVAL AND SECTION A-A RECONSTRUCTION SEE BRIDGE SHEET 7 THROUGH 9.




SUBDIRECTORY	.DGN LOCATOR	SHEET SCALE
BRC	42277phasing	AS NOTED

STATE OF NEW HAMPSHIRE									
DEPARTMENT OF TRANSPORTATION * BUREAU OF BRIDGE DESIGN									
TOWN	WALPOLE, NH - ROCKINGHAM, VT			BRIDGE NO.	058/043		STATE PROJECT	42277	
LOCATION	CHURCH STREET OVER CONNECTICUT RIVER								
ABUTMENT B - STUBWALL SECTIONS								BRIDGE SHEET	
REVISIONS AFTER PROPOSAL				BY	DATE		BY	DATE	6 OF 19
				DESIGNED	JDG	05/2020	CHECKED	JDG	05/2020
				DRAWN	JTB	05/2020	CHECKED	JDG	05/2020
				QUANTITIES	JDG	05/2020	CHECKED	SRW	05/2020
				ISSUE DATE		FEDERAL PROJECT NO.		SHEET NO.	TOTAL SHEETS
				REV. DATE		X-A004(799)		11	31



PHASE 1 STUBWALL PLAN – ABUTMENT B
SCALE: 3/8"=1'-0"




PHASE 1 STUBWALL ELEVATION – ABUTMENT B
SCALE: 3/8"=1'-0"

- NOTES:
1. F.G. ELEVATIONS ARE AT FACE OF STUBWALL.
 2. FOR SECTION A-A SEE BRIDGE SHEET 6.
- INDICATES BACKWALL REMOVAL


STATE OF NEW HAMPSHIRE									
DEPARTMENT OF TRANSPORTATION * BUREAU OF BRIDGE DESIGN									
TOWN	WALPOLE, NH - ROCKINGHAM, VT				BRIDGE NO.	058/043		STATE PROJECT	42277
LOCATION	CHURCH STREET OVER CONNECTICUT RIVER								
ABUTMENT B - STUBWALL PHASING 1 OF 3									BRIDGE SHEET
REVISIONS AFTER PROPOSAL					BY	DATE		BY	DATE
				DESIGNED	JDG	05/2020	CHECKED	JDG	05/2020
				DRAWN	JTB	05/2020	CHECKED	JDG	05/2020
				QUANTITIES	JDG	05/2020	CHECKED	SRW	05/2020
				ISSUE DATE		FEDERAL PROJECT NO.		SHEET NO.	TOTAL SHEETS
				REV. DATE		X-A004(799)		12	31



SUBDIRECTORY	DGN LOCATOR	SHEET SCALE
BRC	42277phasing	AS NOTED



PHASE 2 STUBWALL PLAN - ABUTMENT B
SCALE: $\frac{3}{8}" = 1' - 0"$



PHASE 2 STUBWALL ELEVATION - ABUTMENT B
SCALE: $\frac{3}{8}" = 1' - 0"$



- NOTES:
1. F.G. ELEVATIONS ARE AT FACE OF STUBWALL.
 2. FOR SECTION A-A SEE BRIDGE SHEET 6.

 INDICATES BACKWALL REMOVAL


STATE OF NEW HAMPSHIRE									
DEPARTMENT OF TRANSPORTATION * BUREAU OF BRIDGE DESIGN									
TOWN WALPOLE, NH - ROCKINGHAM, VT			BRIDGE NO. 058/043		STATE PROJECT 42277				
LOCATION CHURCH STREET OVER CONNECTICUT RIVER									
ABUTMENT B - STUBWALL PHASING 2 OF 3								BRIDGE SHEET	
REVIEWS AFTER PROPOSAL			BY DATE		BY DATE		8 OF 19		
			DESIGNED JDG 05/2020		CHECKED JDG 05/2020		FILE NUMBER		
			DRAWN JTB 05/2020		CHECKED JDG 05/2020				
			QUANTITIES JDG 05/2020		CHECKED SRW 05/2020				
			ISSUE DATE		FEDERAL PROJECT NO.		SHEET NO.		TOTAL SHEETS
			REV. DATE		X-A004(799)		13		31



SUBDIRECTORY	.DGN LOCATOR	SHEET SCALE
BRC	42277phasing	AS NOTED



PHASE 3 STUBWALL PLAN - ABUTMENT B
SCALE: 3/8"=1'-0"



PHASE 3 STUBWALL ELEVATION - ABUTMENT B
SCALE: 3/8"=1'-0"


- NOTES:
1. F.G. ELEVATIONS ARE AT FACE OF STUBWALL.
 2. FOR SECTION A-A SEE BRIDGE SHEET 6.

 INDICATES BACKWALL REMOVAL




SUBDIRECTORY	DGN LOCATOR	SHEET SCALE
BRC	42277phasing	AS NOTED

STATE OF NEW HAMPSHIRE									
DEPARTMENT OF TRANSPORTATION * BUREAU OF BRIDGE DESIGN									
TOWN	WALPOLE, NH - ROCKINGHAM, VT	BRIDGE NO.	058/043	STATE PROJECT	42277	BRIDGE SHEET			
LOCATION	CHURCH STREET OVER CONNECTICUT RIVER	ABUTMENT B - STUBWALL PHASING 3 OF 3				9 OF 19			
REVISIONS AFTER PROPOSAL		BY	DATE	CHECKED	DATE	FILE NUMBER			
		DESIGNED	JDG	05/2020	JDG	05/2020			
		DRAWN	JTB	05/2020	JDG	05/2020			
		QUANTITIES	JDG	05/2020	SRW	05/2020			
		ISSUE DATE		FEDERAL PROJECT NO.		SHEET NO.	TOTAL SHEETS		
		REV. DATE		X-A004(799)		14	31		




STUBWALL PLAN - ABUTMENT B

SCALE: 3/8"=1'-0"



ABUTMENT BACKWALL PLAN - ABUTMENT B

SCALE: 3/8"=1'-0"



DECK PLAN - ABUTMENT B

SCALE: 3/8"=1'-0"


NOTE:

- FOR SECTION A-A, B-B, C-C, D-D, E-E & F-F SEE BRIDGE SHEET 11.
- SEE BRIDGE SHEET 12 SECTION B-B FOR SIDEWALK AND CURB REINFORCING PLACEMENT.


STATE OF NEW HAMPSHIRE											
DEPARTMENT OF TRANSPORTATION * BUREAU OF BRIDGE DESIGN											
TOWN	WALPOLE, NH - ROCKINGHAM, VT				BRIDGE NO.		058/043		STATE PROJECT	42277	
LOCATION										CHURCH STREET OVER CONNECTICUT RIVER	
ABUTMENT B - STUBWALL REINFORCEMENT 1 OF 2										BRIDGE SHEET	
REVISIONS AFTER PROPOSAL				BY		DATE		BY		DATE	
				DESIGNED	JDG	05/2020		CHECKED	JDG	05/2020	
				DRAWN	JTB	05/2020		CHECKED	JDG	05/2020	
				QUANTITIES	JDG	05/2020		CHECKED	SRW	05/2020	
				ISSUE DATE		FEDERAL PROJECT NO.		SHEET NO.		TOTAL SHEETS	
				REV. DATE		X-A004(799)		15		31	




SUBDIRECTORY	.DGN LOCATOR	SHEET SCALE
BRC	42277phasing	AS NOTED




SECTION A-A STUBWALL
SCALE: 1" = 1'-0"




SECTION B-B BACKWALL
SCALE: 1" = 1'-0"




SECTION C-C DECK
SCALE: 1" = 1'-0"



SECTION D-D STUBWALL
SCALE: 1" = 1'-0"



SECTION E-E
SCALE: 3/8"=1'-0"



SECTION F-F
SCALE: 3/8"=1'-0"



NOTE:

1. FOR LOCATION OF SECTION A-A, B-B, C-C, D-D, E-E & F-F SEE BRIDGE SHEET 10.



SUBDIRECTORY	.DGN LOCATOR	SHEET SCALE
BRC	42277phasing	AS NOTED


STATE OF NEW HAMPSHIRE									
DEPARTMENT OF TRANSPORTATION * BUREAU OF BRIDGE DESIGN									
TOWN	WALPOLE, NH - ROCKINGHAM, VT	BRIDGE NO.	058/043	STATE PROJECT	42277	BRIDGE SHEET			
LOCATION	CHURCH STREET OVER CONNECTICUT RIVER	ABUTMENT B - STUBWALL REINFORCEMENT 2 OF 2				11 OF 19			
REVISIONS AFTER PROPOSAL		BY	DATE	CHECKED	DATE	FILE NUMBER			
		JDG	05/2020	JDG	05/2020				
		JTB	05/2020	JDG	05/2020				
		JDG	05/2020	SRW	05/2020				
		ISSUE DATE		FEDERAL PROJECT NO.	SHEET NO.	TOTAL SHEETS			
		REV. DATE		X-A004(799)	16	31			



DECK PLAN - PIER 1

(EXISTING LONGITUDINAL REINFORCING TO BE RETAINED NOT SHOWN FOR CLARITY)

SCALE: 1/2" = 1'-0"



SECTION B-B



SCALE: 1" = 1'-0"

NOTE:
1. FOR SECTION A-A SEE BRIDGE SHEET 13.

STATE OF NEW HAMPSHIRE											
DEPARTMENT OF TRANSPORTATION * BUREAU OF BRIDGE DESIGN											
TOWN	WALPOLE, NH - ROCKINGHAM, VT				BRIDGE NO.		058/043		STATE PROJECT	42277	
LOCATION										CHURCH STREET OVER CONNECTICUT RIVER	
DECK REINFORCING - PIER 1										BRIDGE SHEET	
REVISIONS AFTER PROPOSAL				BY	DATE		BY	DATE		12 OF 19	
				DESIGNED	GAB	04/2020		CHECKED	PAG	05/2020	FILE NUMBER
				DRAWN	JTB	05/2020		CHECKED	PAG	05/2020	
				QUANTITIES	PAG	05/2020		CHECKED	PAG	05/2020	
				ISSUE DATE		FEDERAL PROJECT NO.			SHEET NO.		TOTAL SHEETS
				REV. DATE		X-A004(799)			17		31




SUBDIRECTORY	.DGN LOCATOR	SHEET SCALE
BRC	42277Pier1reinf	AS NOTED



EXPANSION JOINT NOTES

- EXPANSION JOINT STEEL SHALL BE AASHTO M223 (ASTM A572) GR 50. MINOR STEEL PLATES MAY CONFORM TO AASHTO M183 (ASTM A36). ALL STEEL SHALL BE GALVANIZED. THE ENTIRE ASSEMBLY SHALL BE PAID AS ITEM 561.3001, PREFABRICATED FINGER EXPANSION JOINT (F).
- BOLTS IN THE CURBS OR SIDEWALKS SHALL BE STAINLESS STEEL COUNTERSUNK HEAD BOLTS WITH SOCKET HEADS AND SHALL CONFORM TO ASTM A276, TYPE 304. BOLTS IN THE ROADWAY SHALL BE GALVANIZED HIGH-STRENGTH BOLTS AND SHALL CONFORM TO ASTM A325.
- SPLICES FOR EXPANSION JOINT STEEL SHALL DEVELOP FULL STRENGTH.
- THE EXPANSION JOINT SHALL BE PRESET TO THE TEMPERATURE ANTICIPATED AT THE TIME OF INSTALLATION. FINAL SETTING IN THE FIELD SHALL BE DETERMINED BY THE CONTRACT ADMINISTRATOR (SEE TEMPERATURE ADJUSTMENT TABLE). THE MAXIMUM FACTORED MOVEMENT IS 5 3/8 INCHES.
- PROTECT TOP OF EXPANSION JOINT DURING PLACEMENT OF CONCRETE AND BITUMINOUS PAVEMENT.
- JOINT SUPPORT PLATES SHALL BE SHOP WELDED TO THE EXPANSION JOINT STEEL AND SHALL BE VERTICAL AFTER THE JOINT ASSEMBLY HAS BEEN ADJUSTED FOR ROADWAY CROSS-SLOPE AND PROFILE GRADE.
- FASCIA AND CURB PLATES SHALL BE SHOP WELDED AND SHALL BE VERTICAL AFTER THE JOINT ASSEMBLY HAS BEEN ADJUSTED FOR ROADWAY CROSS-SLOPE AND GRADE.
- IMMEDIATELY AFTER THE JOINT HAS BEEN SECURED TO THE STRUCTURAL STEEL, REMOVE SHIPPING DEVICES. WELDING OF SHIPPING DEVICES TO THE FINGER PLATE SHALL NOT BE ALLOWED.
- THE FINGER PLATES SHALL BE CUT FROM ONE CONTINUOUS 2'-1 1/4" WIDE x 2 1/4" THICK PLATE AS SHOWN ON THE FINGER CUTTING DETAIL.
- ELEVATIONS SHOWN AT THE TOP OF FINGER PLATES ARE 1/8" LOWER THAN THE PROPOSED FINISHED ROADWAY GRADE.
- SEE BRIDGE SHEET 15 FOR DOWNSPOUT DETAILS AND NOTES.
- THE FABRIC TROUGH SHALL BE PREFORMED FABRIC MATERIAL AND SHALL BE CUT DURING SHOP PRE-ASSEMBLY. THE TROUGH MAY BE SUPPLIED IN 4 LENGTHS WITH 1'-0" OVERLAP AT PHASING LINES AND AT THE CROWN.
- TRIM EXCESS FABRIC BEHIND CURB PLATES.
- AFTER BOLT INSTALLATION, FILL COUNTERSUNK HOLES WITH ITEM 562.1, SILICONE JOINT SEALANT (F) (APPROX. 1 LF/HOLE).



SECTION A-A

SCALE: 3"=1'-0"

TEMPERATURE ADJUSTMENT TABLE

TEMPERATURE	"T"
15°F	14"
30°F	13 1/16"
45°F	12 5/16"
60°F	12 3/8"
75°F	11 7/8"
90°F	11 5/16"

SUBDIRECTORY	DGN LOCATOR	SHEET SCALE
BRC	42277FingerJt	AS NOTED



STATE OF NEW HAMPSHIRE									
DEPARTMENT OF TRANSPORTATION * BUREAU OF BRIDGE DESIGN									
TOWN	WALPOLE, NH - ROCKINGHAM, VT	BRIDGE NO.	058/043	STATE PROJECT	42277	BRIDGE SHEET			
LOCATION	CHURCH STREET OVER CONNECTICUT RIVER	FINGER PLATE EXPANSION JOINT DETAILS (1 OF 3)				13 OF 19			
REVISIONS AFTER PROPOSAL		BY	DATE	CHECKED	PAG	BY	DATE	FILE NUMBER	
		GAB	04/2020	JTB	05/2020				
		JTB	05/2020	PAG	05/2020				
		PAG	05/2020	PAG	05/2020				
		ISSUE DATE		FEDERAL PROJECT NO.		SHEET NO.		TOTAL SHEETS	
		REV. DATE		X-A004(799)		18		31	

ADJUSTABLE EXPANSION JOINT ANCHOR SYSTEM







SCALE: 1 1/2" = 1'-0"

OUTSIDE VERTICAL CURB PLATE DETAIL

SCALE: 1 1/2" = 1'-0"

STIFFENER PLATE

SCALE: 3" = 1'-0"









PHASE CONSTRUCTION
FIELD WELD SPLICE DETAILS
NOT TO SCALE




SUBDIRECTORY	.DGN LOCATOR	SHEET SCALE
BRC	42277FingerJt	AS NOTED


STATE OF NEW HAMPSHIRE										
DEPARTMENT OF TRANSPORTATION * BUREAU OF BRIDGE DESIGN										
TOWN WALPOLE, NH - ROCKINGHAM, VT			BRIDGE NO. 058/043		STATE PROJECT		42277			
LOCATION CHURCH STREET OVER CONNECTICUT RIVER										
FINGER PLATE EXPANSION JOINT DETAILS (2 OF 3)								BRIDGE SHEET		
								14 OF 19		
								FILE NUMBER		
								TOTAL SHEETS		
								31		
REVISIONS AFTER PROPOSAL			BY		DATE		BY		DATE	
			DESIGNED	GAB	04/2020	CHECKED	PAG	05/2020		
			DRAWN	JTB	05/2020	CHECKED	PAG	05/2020		
			QUANTITIES	PAG	05/2020	CHECKED	PAG	05/2020		
			ISSUE DATE		FEDERAL PROJECT NO.			SHEET NO.		
			REV. DATE		X-A004(799)			19		



<h1 style="text-align: center;">STATE OF NEW HAMPSHIRE</h1> <h2 style="text-align: center;">DEPARTMENT OF TRANSPORTATION * BUREAU OF BRIDGE DESIGN</h2>									
TOWN WALPOLE, NH - ROCKINGHAM, VT			BRIDGE NO. 058/043		STATE PROJECT 42277				
LOCATION CHURCH STREET OVER CONNECTICUT RIVER									
<h3>FINGER PLATE EXPANSION JOINT DETAILS (3 OF 3)</h3>								BRIDGE SHEET 15 OF 19	
REVISED AFTER PROPOSAL			BY DATE		BY DATE		FILE NUMBER		
			DESIGNED GAB 04/2020		CHECKED PAG 05/2020				
			DRAWN JTB 05/2020		CHECKED PAG 05/2020				
			QUANTITIES PAG 05/2020		CHECKED PAG 05/2020				
			ISSUE DATE		FEDERAL PROJECT NO.		SHEET NO.		TOTAL SHEETS
			REV. DATE		X-A004(799)		20		
							31		



PLAN VIEW
SCALE: 1" = 1'-0"




SECTION A-A
SCALE: 2" = 1'-0"


SECTION B-B
SCALE: 3/4" = 1'-0"

SECTION C-C
SCALE: 3/4" = 1'-0"

SECTION D-D
SCALE: 3/4" = 1'-0"




BEARING STRIP DETAIL
NOT TO SCALE



FIELD SPLICE WELD DETAIL

EXPANSION JOINT NOTES

- ALL EXPANSION JOINT STEEL, INCLUDING ANCHORS, SHALL BE GALVANIZED. STEEL ANGLES SHALL BE ASTM A572 GRADE 50. MINOR STEEL PLATES MAY CONFORM TO ASTM A36. THE ENTIRE ASSEMBLY, INCLUDING STRIP SEAL, SHALL BE PAID FOR AS ITEM 561.1001, PREFABRICATED STRIP SEAL EXPANSION JOINT (F).
- SPLICES FOR STEEL ANGLES SHALL DEVELOP FULL STRENGTH.
- EXPANSION JOINT OPENING SHALL BE ADJUSTED TO TEMPERATURE ANTICIPATED JUST PRIOR TO POURING DECK BLOCKOUT. FINAL SETTING IN THE FIELD SHALL BE DETERMINED BY THE CONTRACT ADMINISTRATOR. SEE TEMPERATURE ADJUSTMENT TABLE & NOTES.
- STRIP SEAL SHALL BE FURNISHED IN ONE CONTINUOUS LENGTH. NO SPLICES WILL BE ALLOWED. SEAL SHALL BE INSTALLED IN THE FIELD BY THE CONTRACTOR, IN ACCORDANCE WITH THE MANUFACTURER OF THE SEAL, USING AN APPROVED TOOL THAT WILL NOT DAMAGE THE SEAL.
- JOINT SUPPORT PLATES AND CURB PLATES SHALL BE SHOP WELDED TO EXPANSION JOINT STEEL AND SHALL BE NORMAL TO GRADE AFTER JOINT ASSEMBLY HAS BEEN ADJUSTED FOR ROADWAY CROSS-SLOPE AND GRADE. STEEL ANGLES AND EXTRUSIONS SHALL BE ASSEMBLED WITH A CONSTANT JOINT OPENING TO ENSURE PROPER PERFORMANCE AND WATER TIGHTNESS.
- THE EXPANSION JOINT ASSEMBLY SHALL BE INSTALLED ONLY AFTER BOTH ABUTMENTS HAVE BEEN BACKFILLED TO WITHIN 3'-0" OF FINISHED GRADE.
- IMMEDIATELY AFTER THE JOINT HAS BEEN SECURED TO THE STRUCTURAL STEEL AND BACKWALL, REMOVE SHIPPING DEVICES AND GRIND SMOOTH ANY WELDS ON EXPOSED SURFACES. REPAIR ANY DAMAGE TO GALVANIZED SURFACES IN ACCORDANCE WITH SECTION 550.
- PROTECT TOP OF EXPANSION JOINT DURING PLACEMENT OF CONCRETE AND BITUMINOUS PAVEMENT.
- THE STRIP SEAL HAS BEEN DESIGNED FOR A TOTAL FACTORED MOVEMENT OF 2.1 INCHES. DESIGN INCLUDES MOVEMENT DUE TO TEMPERATURE, SKEW, SHRINKAGE AND MINIMUM INSTALLATION WIDTH. THE CONTRACTOR SHALL USE AN SE-400 SEAL BY WATSON BOWMAN OR A2R-400 BY D.S. BROWN, AS NOTED IN THE OPL.
- ELEVATIONS SHOWN AT TOP OF ANGLES ARE 1/8" LOWER THAN PROPOSED FINISHED ROADWAY GRADE.
- NO "LOW PROFILE" STEEL EXTRUSIONS SHALL BE ALLOWED. SEE OPL FOR APPROVED PRODUCTS.
- PRIOR TO INSTALLING THE SEAL, ALL TEMPORARY FORM WORK SHALL BE REMOVED. STEEL ANGLES AND EXTRUSIONS SHALL BE MAINTAINED FREE FROM DIRT, WATER AND ANY OTHER LOOSE DEBRIS, WITH THE USE OF COMPRESSED AIR, TO ENSURE PROPER FIT OF THE SEAL. CARE SHALL BE TAKEN NOT TO DAMAGE GALVANIZED SURFACES.
- A TEMPORARY SEAL(S) SHALL BE INSTALLED PRIOR TO THE START OF THE WINTER MAINTENANCE PERIOD FOR ALL JOINT ASSEMBLIES OR PORTIONS THEREOF THAT WILL BE IN PLACE THROUGHOUT THE WINTER. ALL TEMPORARY SEALS SHALL BE REMOVED AND JOINT OPENINGS AND SUBSTRUCTURE SHALL BE CLEANED PRIOR TO INSTALLING THE FINAL SEAL. ALL COSTS SHALL BE SUBSIDIARY TO ITEM 561.1001.



ANCHOR DETAIL (90° CROSSING)
SCALE: 3" = 1'-0"


TEMPERATURE ADJUSTMENT NOTES

- "T" DIMENSIONS ARE PERPENDICULAR TO FACE OF BACKWALL.
- MINIMUM "T" WIDTH FOR SEAL INSTALLATION = 1 3/4" (APPROXIMATELY 65°F OR LESS).
- VALUES IN THE TEMPERATURE ADJUSTMENT TABLE ARE FOR SETTING THE EXPANSION JOINT ASSEMBLY IMMEDIATELY PRIOR TO POURING THE DECK BLOCKOUT.



TEMPERATURE ADJUSTMENT TABLE	
TEMPERATURE	"T"
20°F	2 3/8"
35°F	2 3/16"
50°F	1 15/16"
65°F	1 3/4"
80°F	1 3/16"
95°F	1 5/16"

SUBDIRECTORY	DGN LOCATOR	SHEET SCALE
English/EXP-J45277	STRIP_SEAL-BKWLL	PANELAS NOTED


STATE OF NEW HAMPSHIRE									
DEPARTMENT OF TRANSPORTATION * BUREAU OF BRIDGE DESIGN									
TOWN	WALPOLE, NH - ROCKINGHAM, VT				BRIDGE NO.	058/043		STATE PROJECT	42277
LOCATION		CHURCH STREET OVER THE CONNECTICUT RIVER							
STRIP SEAL EXPANSION JOINT									BRIDGE SHEET
	REVISIONS AFTER PROPOSAL				BY	DATE		BY	DATE
				DESIGNED	JGS	9/2019	CHECKED	JDG	05/2020
				DRAWN	LRB	10/2019	CHECKED	JDG	05/2020
				QUANTITIES	JDG	05/2020	CHECKED	SRW	05/2020
				ISSUE DATE	FEDERAL PROJECT NO.			SHEET NO.	
				REV. DATE	X-A004(799)			21	31
									16 OF 19
									FILE NUMBER
									TOTAL SHEETS




PARTIAL ASSEMBLY DETAIL
SCALE: 3/4" = 1'-0"



SECTION B-B
SCALE: 3/4" = 1'-0"



SECTION C-C
SCALE: 3/4" = 1'-0"



SECTION D-D
SCALE: 3/4" = 1'-0"

STATE OF NEW HAMPSHIRE									
DEPARTMENT OF TRANSPORTATION * BUREAU OF BRIDGE DESIGN									
TOWN	WALPOLE, NH - ROCKINGHAM, VT				BRIDGE NO.	058/043		STATE PROJECT	42277
LOCATION CHURCH STREET OVER THE CONNECTICUT RIVER									
SIDEWALK PLATE DETAILS									BRIDGE SHEET
REVISIONS AFTER PROPOSAL				BY	DATE		BY	DATE	
				DESIGNED	JGS	9/2019		CHECKED	JDG 05/2020
				DRAWN	LRB	10/2019		CHECKED	JDG 05/2020
				QUANTITIES	JDG	05/2020		CHECKED	SRW 05/2020
				ISSUE DATE		FEDERAL PROJECT NO.		SHEET NO.	TOTAL SHEETS
				REV. DATE		X-A004(799)		22	31
17 OF 19									
FILE NUMBER									

SUBDIRECTORY	.DGN LOCATOR	SHEET SCALE
English/EXP-JTS	42277Exp Jt Sidewalk Plates	AS NOTED

ABUTMENT B - STUBWALL REINFORCEMENT					BRIDGE SHEET 10 OF 19											
Mark	Size	Length	# Pieces	Type	A	B	C	D	E	F	G	H	J	K	R	O
SW01	#5	2.50	96	—												
SW02	#5	6.24	49	17		2.58	1.08	2.58								
SW03	#5	20.92	8	—												
SW04	#5	11.08	8	—												
SW05	#5	15.25	8	—												
SW06	#5	7.92	3	S6	0.83	2.58	1.08	2.58			0.83					
SW07	#4	9.83	3	S5	0.67	0.83	6.83	0.83			0.67					
SW08	#4	4.58	3	S5	0.67	0.83	1.58	0.83			0.67					
SW09	#5	3.00	16	C1												
SW10	#5	3.00	16	C2												
SW11	#4	4.67	6	N10		1.50	1.67	1.50				1.08	1.08	1.08	1.08	
A01	#5	3.00	10	C1												
A02	#5	3.00	10	C2												
A03	#5	20.92	5	—												
A04	#5	11.08	5	—												
A05	#5	15.25	5	—												
A06	#5	2.08	50	17		0.50	1.08	0.50								
A07	#4	5.37	2	N11	1.50	0.35	1.67	0.35	1.50			0.25	0.25	0.25	0.25	
S01	#5	4.63	139	—												
S02	#5	6.17	50	S6	0.00	0.75	3.67	0.92			0.83					
S03	#5	9.83	10	S5	0.67	0.83	6.83	0.83			0.67					
S04	#5	4.58	10	S5	0.67	0.83	1.58	0.83			0.67					
S05	#6	3.83	40	C1												
S06	#6	3.83	40	C2												
S07	#6	20.92	20	—												
S08	#6	11.08	20	—												
S09	#6	15.25	20	—												
S10	#4	4.63	17	—												
SECTION SUMMARY TOTAL WEIGHT (lbs):																
ITEM #	DESCRIPTION	#3	#4	#5	#6	#7	#8	#9	#10	#11	#14	#18	TOTAL			
544	REINFORCING STEEL	0	0	0	0	0	0	0	0	0	0	0	0			
544.11	MECH. CONNECTOR	0	0	0	0	0	0	0	0	0	0	0	0			
544.2	EPOXY COATED	0	107	2486	1419	0	0	0	0	0	0	0	4013			
544.21	EPOXY MECH. CON.	0	0	163	461	0	0	0	0	0	0	0	623			
DECK REINFORCING - PIER 1					BRIDGE SHEET 12 OF 19											
Mark	Size	Length	# Pieces	Type	A	B	C	D	E	F	G	H	J	K	R	O
D01E	#6	20.83	16	—												
D02E	#6	11.17	16	—												
D03E	#6	15.17	16	—												
D04E	#6	3.00	32	C1												
D05E	#6	3.00	32	C2												
D06E	#5	6.83	32	—												
D07E	#5	4.17	8	C1												
D08E	#5	2.67	8	C2												
D09E	#5	1.17	8	C1												
D10E	#5	5.67	8	C2												
D11E	#5	4.33	60	N2		0.58	0.83	1.67	1.25			0.92		0.92		
D12E	#4	2.75	17	—												
D13E	#4	3.25	17	—												
D14E	#4	11.25	9	S5	1.25	1.50	6.83	1.17			0.50					
D15E	#4	5.92	9	S5	1.25	1.42	1.58	1.17			0.50					
SECTION SUMMARY TOTAL WEIGHT (lbs):																
ITEM #	DESCRIPTION	#3	#4	#5	#6	#7	#8	#9	#10	#11	#14	#18	TOTAL			
544	REINFORCING STEEL	0	0	0	0	0	0	0	0	0	0	0	0			
544.11	MECH. CONNECTOR	0	0	0	0	0	0	0	0	0	0	0	0			
544.2	EPOXY COATED	0	171	499	1134	0	0	0	0	0	0	0	1804			
544.21	EPOXY MECH. CON.	0	0	114	288	0	0	0	0	0	0	0	402			

STANDARD INDUSTRY BENDS, STIRRUPS, & TIES

RECOMMENDED END HOOKS ALL GRADES (IN)

BAR SIZE	D	180° HOOKS	90° HOOKS
	Φ	A.G	J
#3	2 1/4	5	3
#4	3	6	4
#5	3 3/4	7	5
#6	4 1/2	8	6
#7	5 1/4	10	7
#8	6	11	8
#9	9 1/2	15	11 3/4
#10	10 3/4	17	13 1/4
#11	12	19	14 3/4
#14	18 1/4	27	21 3/4

STIRRUP & TOE HOOK DIMENSIONS ALL GRADES (IN)

BAR SIZE	D	90° HOOKS	135° HOOKS
	Φ	A.G	A.G
#3	1 1/2	4	4
#4	2	4 1/2	4 1/2
#5	2 1/2	6	5 1/2
#6	4 1/2	12	7 3/4
#7	5 1/4	14	9
#8	6	16	10 1/4

NOTE: D = finished inside bend d of hook. For additional data on standard bar bends not shown on this sheet see current CRS1 Manual.

STANDARD N.H. & SPECIAL BENDS

NOTES:

1. FIGURES IN CIRCLE SHOW TYPE OF BEND.

2. UNLESS OTHERWISE DESIGNATED, ALL BAR REINFORCEMENT FOR CONCRETE IN SIZES UP TO AND INCLUDING #18 SHALL CONFORM TO THE REQUIREMENTS OF THE "SPECIFICATIONS FOR DEFORMED BILLET - STEEL BARS FOR CONCRETE REINFORCEMENT", AASHTO M 31-94 (ASTM A615).

3. FOR TYPICAL BENDING DETAILS, RECOMMENDED PIN DIAMETER "D" OF BENDS AND HOOKS AND OTHER STANDARD PRACTICE REFER TO THE CURRENT CONCRETE REINFORCING STEEL INSTITUTE "MANUAL OF STANDARD PRACTICE".

4. BARS WHICH REQUIRE MORE ACCURATE BENDING THAN STANDARD PRACTICES SHOULD HAVE LIMITS INDICATED.

5. ALL DIMENSIONS ARE OUT TO OUT OF BAR EXCEPT "A" AND "G" ON STANDARD 180° AND 135° HOOKS.

6. "J" DIMENSION ON 180° HOOKS TO BE SHOWN ONLY WHEN NECESSARY TO RESTRICT HOOK SIZE, OTHERWISE STANDARD HOOKS ARE TO BE USED.

7. "H" DIMENSION ON STIRRUPS TO BE SHOWN ONLY WHEN NECESSARY TO MAINTAIN CLEARANCES.

8. WHERE SLOPE DIFFERS FROM 45° DIMENSIONS "H" AND "K" MUST BE SHOWN.

▲ DENOTES BARS TO BE CUT IN FIELD, AS REQUIRED.

▲ DENOTES BARS TO BE BENT IN FIELD.

ASTM STANDARD REINFORCING BARS

BAR SIZE	WEIGHT LBS/FT	DIAM IN	CROSS SECT AREA IN²
#3	0.376	0.375	0.11
#4	0.668	0.500	0.20
#5	1.043	0.625	0.31
#6	1.502	0.750	0.44
#7	2.044	0.875	0.60
#8	2.670	1.000	0.79
#9	3.400	1.128	1.00
#10	4.303	1.270	1.27
#11	5.313	1.410	1.56
#14	7.650	1.693	2.25
#18	13.600	2.257	4.00

SUBDIRECTORY

.DGN LOCATOR

SHEET SCALE

BRC

42277reinf.scht

AS NOTED

STATE OF NEW HAMPSHIRE

DEPARTMENT OF TRANSPORTATION * BUREAU OF BRIDGE DESIGN

TOWN

WALPOLE, NH - ROCKINGHAM, VT

BRIDGE NO.

058/043

STATE PROJECT

42277

LOCATION

CHURCH STREET OVER CONNECTICUT RIVER

REINFORCING SCHEDULE

REVISIONS AFTER PROPOSAL

BY

DATE

CHECKED

DATE

DESIGNED

JDG

05/2020

CHECKED

JDG

05/2020

DRAWN

JTB

05/2020

CHECKED

JDG

05/2020

QUANTITIES

JDG

05/2020

CHECKED

JDG

05/2020

ISSUE DATE

FEDERAL PROJECT NO.

X-A004(799)

SHEET NO.

23

TOTAL SHEETS

31

BRIDGE SHEET


18 OF 19

FILE NUMBER


STATE OF NEW HAMPSHIRE									
DEPARTMENT OF TRANSPORTATION * BUREAU OF BRIDGE DESIGN									
TOWN	WALPOLE, NH - ROCKINGHAM, VT			BRIDGE NO.	058/043		STATE PROJECT	42277	
LOCATION	CHURCH STREET OVER CONNECTICUT RIVER								
ALUMINUM BRIDGE RAIL (3-BAR)									BRIDGE SHEET
REVISIONS AFTER PROPOSAL				BY	DATE	BY	DATE	19 OF 19	
			DESIGNED	JGS	9/2019	CHECKED	JDG	05/2020	FILE NUMBER
			DRAWN	LRB	10/2019	CHECKED	JDG	05/2020	
			QUANTITIES	JDG	05/2020	CHECKED	SRW	05/2020	
			ISSUE DATE		FEDERAL PROJECT NO.		SHEET NO.		TOTAL SHEETS
			REV. DATE		X-A004(799)		24		31

PHASING NOTES

1. TO CONSTRUCT EXPANSION JOINT SHORT TERM TEMPORARY RELOCATION OF THE SIDEWALK WILL BE REQUIRED. TEMPORARY WOODEN BRIDGE OR STEEL PLATE OVER THE GAP CAN BE UTILIZED TO AVOID A FIELD SPLICE. ALL TEMPORARY PEDESTRIAN FACILITIES SHALL MEET ADA REQUIREMENTS.






STATE OF NEW HAMPSHIRE			
DEPARTMENT OF TRANSPORTATION • BUREAU OF HIGHWAY DESIGN			
TRAFFIC CONTROL 1			
DGN	STATE PROJECT NO.	SHEET NO.	TOTAL SHEETS
42277tc	42277	25	31



STATE OF NEW HAMPSHIRE			
DEPARTMENT OF TRANSPORTATION • BUREAU OF HIGHWAY DESIGN			
TRAFFIC CONTROL 2			
DGN	STATE PROJECT NO.	SHEET NO.	TOTAL SHEETS
42277+c	42277	26	31

TEMPORARY TRAFFIC SIGNAL PHASING DIAGRAM





















TEMPORARY TRAFFIC SIGNAL NOTES

- TEMPORARY TRAFFIC SIGNALS SHALL BE LOCATED ON THE NH SIDE USING MOBILE UNITS AND/ OR TEMPORARY POLES AS SHOWN ON THE PLAN AND IN COMPLIANCE WITH THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (MUTCD). AS CONSTRUCTION PHASING REQUIRES THE TRAFFIC SIGNAL HEAD LOCATIONS ON THE NH SIDE MAY REQUIRE ADJUSTMENTS.
- THE TEMPORARY SIGNALS ON THE VT SIDE SHALL BE WIRED TO THE EXISTING TCT 3000-E CONTROLLER ON THE NH SIDE TO PROVIDE THE CONCURRENT OPERATION AS SHOWN IN THE PHASING DIAGRAM.
- ON THE NH SIDE THE RIVER STREET APPROACH STOP BAR SHALL BE RELOCATED TO THE EAST OF THE RR TRACKS AND TEMPORARY DETECTION SHALL BE PROVIDED.
- ON THE VT SIDE, DETECTION SHALL BE PROVIDED FOR THE ROCKINGHAM ROAD APPROACHES TO EXTEND PHASE 2. (NO DETECTION IS REQUIRED ON THE BRIDGE APPROACH AS THIS PHASE IS RECALLED AND EXTENDED WITH DETECTION ON THE NH SIDE.)
- TIMING OF THE TRAFFIC SIGNAL WILL BE IN ACCORDANCE WITH THE EXISTING TIMING PLAN FOR THE NH-12 AT CHURCH ST TRAFFIC SIGNAL AND ADJUSTED AS REQUIRED IN THE FIELD AND DIRECTED BY THE RESIDENT ENGINEER.

WALPOLE NH RTE 12 AT CHURCH ST CABINET - M TYPE 1 TCT CONTROLLER - PEEK 3000E				SIG ID: S-461-01	
TRAFFIC SIGNAL TIMING					
	PHASE 1	PHASE 2	PHASE 3	PHASE 4	
		CHURCH ST		RR PREEMPT	
MINIMUM	10	5			
EXTENSION	5	4			
MAXIMUM	30	30			
YELLOW	4	4			
ALL RED	2	2			
WALK			7		
FLASHING DON'T WALK			30		
RECALL	ON	NL			
NOTES: PE1 = 2+4RR OLA=2					



STATE OF NEW HAMPSHIRE			
DEPARTMENT OF TRANSPORTATION • BUREAU OF HIGHWAY DESIGN			
TEMPORARY SIGNAL PLAN			
DGN	STATE PROJECT NO.	SHEET NO.	TOTAL SHEETS
42277+c	42277	27	31

ITEM #	IDENT #	SIGN SIZE		TEXT	TEXT DIMENSIONS			SHIELD SIZE (inch)	ARROW (inch)	NUMERAL (inch)	# SIGNS REQ'D	SIGN AREA (SQ. FT.)		POSTS PER SIGN					REMARKS	ITEM #	IDENT #	SIGN SIZE		TEXT	TEXT DIMENSIONS			SHIELD SIZE (inch)	ARROW (inch)	NUMERAL (inch)	# SIGNS REQ'D	SIGN AREA (SQ. FT.)		POSTS PER SIGN					REMARKS	
		WIDTH (inch)	HEIGHT (inch)		UC	LC	CAPS					NOM AREA	TOTAL AREA	BREAKAWAY	STEEL I-BEAM	CONCRETE BASE	4" ALUMINUM	U-CHANNEL-GALV.				WIDTH (inch)	HEIGHT (inch)		UC	LC	CAPS					NOM AREA	TOTAL AREA	BREAKAWAY	STEEL I-BEAM	CONCRETE BASE	4" ALUMINUM	U-CHANNEL-GALV.		
619.1	W20-1C	48	48				7D				4	16.0	64.0						2	BLACK / ORANGE	619.1	M6-3	21	15								8	2.19	17.50						BLACK / ORANGE MOUNT WITH DETOUR ROUTE ASSEMBLY
619.1	W20-1e	48	48				7D				4	16.0	64.0						2	BLACK / ORANGE	619.1	M4-6	24	12				6D				2	2.00	4.00						BLACK / ORANGE MOUNT WITH DETOUR ROUTE ASSEMBLY
619.1	G20-2d	36	18				4C				4	4.50	18.00						2	BLACK / ORANGE	619.1	M6-1L	21	15								5	2.19	10.94						BLACK / ORANGE MOUNT WITH DETOUR ROUTE ASSEMBLY
619.1	R9-11a	24	12				2C				2	2.00	4.00						2	BLACK / WHITE MOUNTED ON BARRICADE	619.1	M6-1R	21	15								1	2.19	2.19						BLACK / ORANGE MOUNT WITH DETOUR ROUTE ASSEMBLY
619.1	R5-2a (M)	36	36				7D 6D 6D				4	9.00	36.00						2	BLACK / WHITE	619.1	M5-2R	21	15								2	2.19	4.38						BLACK / ORANGE MOUNT WITH DETOUR ROUTE ASSEMBLY
619.1	W5-2	48	48				8D				4	16.0	64.0							BLACK / YELLOW MOUNT BELOW R5-2A(M)	619.1	M5-1L	21	15								5	2.19	10.94						BLACK / ORANGE MOUNT WITH DETOUR ROUTE ASSEMBLY
619.1	M4-4	24	12				6C				26	2.00	52.00							BLACK / ORANGE MOUNT WITH DETOUR ROUTE ASSEMBLY	619.1	M5-1R	21	15								1	2.19	2.19						BLACK / ORANGE MOUNT WITH DETOUR ROUTE ASSEMBLY
619.1	M4-8	24	12				6B				26	2.00	52.00							BLACK / ORANGE MOUNT WITH DETOUR ROUTE ASSEMBLY	619.1	M5-2R	21	15								2	2.19	4.38						BLACK / ORANGE MOUNT WITH DETOUR ROUTE ASSEMBLY
619.1	M1-5 (12)	24	24				12D				15	4.00	60.00						2	BLACK /WHITE	<div>GENERAL NOTES</div> <div>1. ALL GUIDE SIGNS SHALL HAVE TYPE III TEXT AND BORDER WITH TYPE III BACKGROUND SHEETING, UNLESS OTHERWISE SPECIFIED. ALL GUIDE SIGNS WITH ITEM NUMBERS 615.01 OR 615.04 (TYPE A & TYPE AA) SHALL HAVE FLAT SHEET DEMOUNTABLE TEXT AND BORDER AS PRESCRIBED IN THE SPECIFICATIONS.</div> <div>2. THERE SHALL BE NO GAPS IN THE BORDERS OF ALL GUIDE SIGNS.</div> <div>3. ALL REGULATORY AND WARNING SIGNS SHALL HAVE TYPE I BACKGROUND SHEETING, UNLESS OTHERWISE SPECIFIED.</div> <div>4. ALL GUIDE SIGNS SHALL CONTAIN THE SIZE AND DATE OF MANUFACTURE, LOCATED IN THE LOWER LEFT CORNER OF THE FRONT FACE. THESE LETTERS AND NUMBERS SHALL BE 2" NON-REFLECTIVE WHITE (I.E., 3-98 10' x 15').</div> <div>5. REFER TO THE "STANDARD HIGHWAY SIGNS MANUAL" AS PUBLISHED BY THE USDOT-FHWA FOR EXACT DETAILS OF BORDERS, ETC.</div> <div>6. REFER TO THE "STANDARD PLANS FOR ROAD AND BRIDGE CONSTRUCTION" AS PUBLISHED BY THE NHDOT FOR EXACT DETAILS OF PERMANENT SIGNING STANDARDS.</div> <div>7. THE MINIMUM SIGN HEIGHT FOR A ROADSIDE SIGN IN A RURAL DISTRICT SHALL BE INCREASED FROM 5 FEET TO 6 FEET. ALL OTHER SIGN HEIGHTS SHALL BE IN ACCORDANCE WITH THE LATEST EDITION OF THE MUTCD.</div>																			
619.1	M1-4 (5)	24	24				12D				11	4.00	44.00						2	BLACK /WHITE																				

STATE OF NEW HAMPSHIRE

DEPARTMENT OF TRANSPORTATION • BUREAU OF TRAFFIC

SIGN TEXT LAYOUT 1

DGN

42277typ

STATE PROJECT NO.

SHEET NO.

28

TOTAL SHEETS


31

ITEM #	IDENT #	SIGN SIZE		TEXT	TEXT DIMENSIONS			SHIELD SIZE (inch)	ARROW (inch)	NUMERAL (inch)	# SIGNS REQ'D	SIGN AREA (SQ. FT.)		POSTS PER SIGN					REMARKS	ITEM #	IDENT #	SIGN SIZE		TEXT	TEXT DIMENSIONS			SHIELD SIZE (inch)	ARROW (inch)	NUMERAL (inch)	# SIGNS REQ'D	SIGN AREA (SQ. FT.)		POSTS PER SIGN					REMARKS
		WIDTH (inch)	HEIGHT (inch)		LETTER HEIGHT (inch)							NOM AREA	TOTAL AREA	BREAKAWAY	STEEL I-BEAM	CONCRETE BASE	4" ALUMINUM	U-CHANNEL-GALV.				WIDTH (inch)	HEIGHT (inch)		LETTER HEIGHT (inch)							NOM AREA	TOTAL AREA	BREAKAWAY	STEEL I-BEAM	CONCRETE BASE	4" ALUMINUM	U-CHANNEL-GALV.	
					UC	LC	CAPS																		UC	LC	CAPS												
619.1		60	12	TRACTOR TRAILERS			5C				5	5.00	25.00						BLACK / ORANGE MOUNT WITH R11-3(M)																				
619.1		60	12	DETOUR AHEAD			5C				5	5.00	25.00						BLACK / ORANGE MOUNT WITH R11-3(M)																				
619.1	R11-3 (M)	60	30	BRIDGE CLOSED 200 FEET AHEAD LOCAL TRAFFIC ONLY			6C 5C 4C				1	12.50	12.50					2	BLACK / WHITE																				
619.1	R11-3 (M)	60	30	BRIDGE CLOSED 500 FEET AHEAD LOCAL TRAFFIC ONLY			6C 5C 4C				1	12.50	12.50					2	BLACK / WHITE																				
619.1	R11-3 (M)	60	30	BRIDGE CLOSED 2 MILES AHEAD LOCAL TRAFFIC ONLY			6C 5C 4C				1	12.50	12.50					2	BLACK / WHITE																				
619.1	R11-3 (M)	60	30	BRIDGE CLOSED 3 MILES AHEAD LOCAL TRAFFIC ONLY			6C 5C 4C				1	12.50	12.50					2	BLACK / WHITE																				
619.1	R11-3 (M)	60	30	BRIDGE CLOSED 4 MILES AHEAD LOCAL TRAFFIC ONLY			6C 5C 4C				1	12.50	12.50					2	BLACK / WHITE																				

GENERAL NOTES

- ALL GUIDE SIGNS SHALL HAVE TYPE III TEXT AND BORDER WITH TYPE III BACKGROUND SHEETING, UNLESS OTHERWISE SPECIFIED. ALL GUIDE SIGNS WITH ITEM NUMBERS 615.01 OR 615.04 (TYPE A & TYPE AA) SHALL HAVE FLAT SHEET DEMOUNTABLE TEXT AND BORDER AS PRESCRIBED IN THE SPECIFICATIONS.
- THERE SHALL BE NO GAPS IN THE BORDERS OF ALL GUIDE SIGNS.
- ALL REGULATORY AND WARNING SIGNS SHALL HAVE TYPE I BACKGROUND SHEETING, UNLESS OTHERWISE SPECIFIED.
- ALL GUIDE SIGNS SHALL CONTAIN THE SIZE AND DATE OF MANUFACTURE, LOCATED IN THE LOWER LEFT CORNER OF THE FRONT FACE. THESE LETTERS AND NUMBERS SHALL BE 2" NON-REFLECTIVE WHITE (I.E., 3-98 10' x 15').
- REFER TO THE "STANDARD HIGHWAY SIGNS MANUAL" AS PUBLISHED BY THE USDOT-FHWA FOR EXACT DETAILS OF BORDERS, ETC.
- REFER TO THE "STANDARD PLANS FOR ROAD AND BRIDGE CONSTRUCTION" AS PUBLISHED BY THE NHDOT FOR EXACT DETAILS OF PERMANENT SIGNING STANDARDS.
- THE MINIMUM SIGN HEIGHT FOR A ROADSIDE SIGN IN A RURAL DISTRICT SHALL BE INCREASED FROM 5 FEET TO 6 FEET. ALL OTHER SIGN HEIGHTS SHALL BE IN ACCORDANCE WITH THE LATEST EDITION OF THE MUTCD.

STATE OF NEW HAMPSHIRE			
DEPARTMENT OF TRANSPORTATION • BUREAU OF TRAFFIC			
SIGN TEXT LAYOUT 2			
DGN	STATE PROJECT NO.	SHEET NO.	TOTAL SHEETS
42277+yp		29	31



PCMS #1
BRIDGE
CLOSED
TO
MESSAGE #1

TRUCKS
STARTING
(DATE)
MESSAGE #2

PUT MESSAGES IN PLACE 4 WEEKS PRIOR
TO START OF PHASED CONSTRUCTION
WORK.

PCMS #2
TRUCKS
TO
NH
MESSAGE #1

USE
EXIT 5
MESSAGE #2

MESSAGE IN PLACE DURING CLOSURE


DETAIL A

DETAIL C


DETAIL B

STATE OF NEW HAMPSHIRE			
DEPARTMENT OF TRANSPORTATION • BUREAU OF HIGHWAY DESIGN			
DETOUR PLAN 1			
DGN	STATE PROJECT NO.	SHEET NO.	TOTAL SHEETS
42277+yp	42277	30	31







DETAIL D




DETAIL F




DETAIL H



DETAIL E



DETAIL G



TRAILBLAZER DETAIL



STATE OF NEW HAMPSHIRE			
DEPARTMENT OF TRANSPORTATION • BUREAU OF HIGHWAY DESIGN			
DETOUR PLAN 2			
DGN	STATE PROJECT NO.	SHEET NO.	TOTAL SHEETS
42277+yp	42277	31	31