

1972 STANDARD SPECIFICATIONS
ERRATA SHEET 1

Please attach this errata sheet inside the front cover of the "1972 Standard Specifications for Highway and Bridge Construction" after making the corrections listed below.

| <u>Page</u> | <u>Line</u> | <u>Change:</u> | <u>To:</u> |
|-------------|-------------|--|-----------------------------------|
| 1-10 | 21 | Medium Cure | Medium Curing |
| 1-10 | 28 | Rapid Cure | Rapid Curing |
| 1-13 | 38 | accuracy of any | accuracy of |
| 1-19 | 18 | paragraph 4 | paragraph (d) |
| 1-30 | 13,14 | in the opinion of | as determined by |
| 1-42 | 13,14 | DELETE: "mounted on a telescopic type staff to provide adequate visibility." | |
| 1-42 | 39,40 | DELETE: "with the staff resting on the ground." | |
| 1-43 | 10,11 | DELETE: "staff vertical and" | |
| 1-62 | 1 | by the barrel | by the hundredweight |
| 1-62 | 1 | term barrel | term sack |
| 1-62 | 1 | 376 | 94 |
| 3-6 | 14 | DELETE: "penetration" | |
| 3-6 | 14,15 | 85-100, 100-120, or 120-150 | AC 5, AC 10 or AC 20 |
| 3-17 | 10 | number of barrels (376 pounds) | amount |
| 3-17 | 10 | cement for | cement in hundredweight for |
| 3-18 | 2 | Barrel | Hundredweight |
| 3-19 | 14 | DELETE: "penetration" | |
| 3-19 | 14 | 85-100 or 100-120 | AC 5 or AC 10 |
| 4-16 | 16 | DELETE: "Penetration" | |
| 4-16 | 16,17 | 85-100, 100-120, or 120-150 | AC 5, AC 10 or AC 20 |
| 4-16 | 17 | DELETE: "penetration" | |
| 4-16 | 30 | 76-84 | 76-94 |
| 4-16 | 36 | DELETE: "No. 100, 2-10, 5-14, 7-17, 7-18" | |
| 4-17 | 7 | in intended | is intended |
| 4-19 | 44 | excepting 0.5 | exceeding 0.5 |
| 4-20 | 31 | the direr | the drier |
| 4-23 | 27 | DELETE: "when Plant Mixed Base Course is specified." | |
| 4-33 | 9 | Pavement will be | Payment will be |
| 5-1 | 15 | 725.02 | 725.01 |
| 5-1 | 19-20 | INSERT: "Polyvinyl Chloride Waterstop - 707.30" | |
| 5-9 | 14 | 6 inches by 36 inches | 6 inches by 6 inches by 36 inches |
| 5-18 | 26 | between the range | within the range |
| 5-33 | 28 | such that | such that the welds |
| 5-37 | 40 | less than 15 | more than 15 |
| 5-48 | 41 | 1200° F. | 1125° F. |
| 5-55 | 26 | 7 inches | 8 inches |
| 5-62 | 40 | after the riveting | after the riveting or welding |
| 6-59 | 30 | for gutters | for curbs, gutters |
| 6-59 | 34 | compliances | compliance |
| 6-67 | 5-6 | INSERT: "616.18 - Granite Bridge Curb (Median Slope Edge) - Linear Feet" | |
| 6-147 | 33 | 675.25...Type A | 675.25...Type B |
| 6-152 | 7-8 | INSERT: "Mortar, Type IV - 707.04" | |
| 6-158 | 7-8 | INSERT: "Mortar, Type IV - 707.04" | |
| 7-6 | 7 | One copy | Both copies |
| 7-6 | 7,8 | DELETE: "accompany each shipment and the other shall" | |