## SUPPLEMENTAL SPECIFICATION

## SECTION 514 - WATER REPELLENT, SILANE

- 514.01 DESCRIPTION. This work shall consist of furnishing and applying a penetrating-type protective sealer on concrete surfaces.
- $\underline{514.02}$  MATERIALS. The material shall be a one-component material consisting of a penetrating-type sealer which does not alter the color or texture of the portland cement concrete.

Acceptable penetrating-type sealers shall be those appearing on the Agency's Approved Products List.

- 514.03 PACKAGING, DELIVERY, AND STORAGE. The material shall be delivered to the project in original, manufacturer's unopened containers and stored in accordance with the manufacturer's recommendations.
- 514.04 PREPARATION OF SURFACES. All surfaces on which the protective sealer is to be applied shall be clean and thoroughly dry to the satisfaction of the Engineer and in accordance with the manufacturer's recommendations. Dirt, grease, curing compounds, asphalt, or other foreign materials shall be removed from the concrete surface before application of the sealer.
- $\underline{514.05}$  APPLICATION. The material shall be applied to the satisfaction of the Engineer and in accordance with the manufacturer's recommendations.
- In the absence of specific recommendations from the manufacturer, the protective sealer shall not be applied to new concrete surfaces that are less than 14 days old. The concrete surfaces shall be free from precipitation for 48 hours prior to application of the sealer. Application of the sealer shall be completed within 40 days of original concrete placement.
- $\underline{514.06}$  PROTECTION. After application of the sealer, the concrete surfaces shall be protected to the satisfaction of the Engineer and in accordance with the manufacturer's recommendations.
- 514.07 METHOD OF MEASUREMENT. The quantity of Water Repellent, Silane to be measured for payment will be the number of liters (gallons) of solution applied in the complete and accepted work, measured to the nearest liter (gallon).
- 514.08 BASIS OF PAYMENT. The accepted quantity of Water Repellent, Silane will be paid for at the Contract unit price per liter (gallon). Payment will be full compensation for furnishing, transporting, handling, and placing the material specified and for furnishing all labor, tools, equipment, and incidentals necessary to complete the work.

Payment will be made under:

Pay Item Pay Unit

514.10 Water Repellent, Silane Liter (Gallon)