

SUBBASE OF CRUSHED GRAVEL, FINE GRADED FOR RECLAIMING

****From Johnson-Hyde Park STP 2215(1)S**

- xx. DESCRIPTION. This work shall consist of furnishing, placing, reclaiming, and grading one or more courses of approved gravel material into a prepared reclaimed stabilized base as shown in the Plans and as directed by the Engineer.

The work under this Section shall be performed in accordance with these provisions and Sections 301 and 310 of the Standard Specifications.

- xx. MATERIALS. Gravel material shall meet the requirements of Section 301 and Subsection 704.05 for Subbase of Crushed Gravel, Fine Graded.

- xx. GENERAL CONSTRUCTION REQUIREMENTS. Gravel material shall be placed on a prepared reclaimed stabilized base at the thickness specified in the Plans or as directed by the Engineer. The material shall be reclaimed into the reclaimed stabilized base. The material shall be worked to improve gradation deficiencies and/or to correct superelevation as directed by the Engineer.

- xx. METHOD OF MEASUREMENT. The quantity of Special Provision (Subbase of Crushed Gravel, Fine Graded for Reclaiming) to be measured for payment will be the number of metric tons (tons) of material in place in the complete and accepted work, as determined from the load tickets.

- xx. BASIS OF PAYMENT. The accepted quantity of Special Provision (Subbase of Crushed Gravel, Fine Graded for Reclaiming) will be paid for at the Contract unit price per metric ton (ton). Payment will be full compensation for furnishing, transporting, placing, and reclaiming the material into the prepared reclaimed stabilized base; for compacting, grading, and testing; and for furnishing all labor, tools, equipment, and incidentals necessary to complete the work.

Payment will be made under:

| <u>Pay Item</u> | <u>Pay Unit</u> |
|---|------------------|
| 900.680 Special Provision (Subbase of Crushed Gravel, Fine Graded for Reclaiming) | Metric Ton (Ton) |