

REMOVAL AND REPLACEMENT OF EXISTING FLUSHING BASIN IN PAVEMENT

**\*\*From Richmond STP 0284(17) Richmond CMG PARK(31)**

xx. DESCRIPTION. This work shall consist of removing and replacing an existing underdrain flushing basin in pavement at the location indicated in the Plans and as directed by the Engineer.

The work under this Section shall be performed in accordance with these provisions, the Plans, and Section 605 of the Standard Specifications.

xx. MATERIALS. Concrete for cast-in-place collar shall meet the requirements of Section 541 for Concrete, Class B.

xx. CONSTRUCTION REQUIREMENTS. The Contractor shall remove and replace the existing flushing basin pipe as detailed in the Contract Documents. The cast iron cover shall be designed to withstand an H-20 loading.

xx. METHOD OF MEASUREMENT. The quantity of Special Provision (Removal and Replacement of Existing Flushing Basin in Pavement) to be measured for payment will be the number of each flushing basin replaced in the complete and accepted work.

xx. BASIS OF PAYMENT. The accepted quantity of Special Provision (Removal and Replacement of Existing Flushing Basin in Pavement) will be paid for at the Contract unit price for each. Payment will be full compensation for removing and disposing of existing flushing basin components; fabricating, furnishing, transporting, handling, and placing the materials specified, including new corrugated pipe, cast-in-place concrete collar, and cast iron frame and cover; and for furnishing all labor, tools, equipment, and incidentals necessary to complete the work.

Payment for new underdrain carrier pipe, including any associated fittings and couplings, will be made separately under Contract item 605.20.

Payment will be made under:

<u>Pay Item</u>	<u>Pay Unit</u>
900.620 Special Provision (Removal and Replacement of Existing Flushing Basin in Pavement)	Each