

ADJUST SIDE INLET CATCH BASIN

****From St. Johnsbury-Lyndon STP 2936(1)**

xx. DESCRIPTION. This work shall consist of adjustment to grade of a catch basin inlet grate using a cast iron riser.

The work under this Section shall be performed in accordance with these provisions, the Plans, and Section 604 of the Standard Specifications.

xx. MATERIALS. Materials for adjusting side inlet catch basin shall meet the requirements of the Plans and Subsection 715.01.

xx. GENERAL REQUIREMENTS. Catch basin(s) shall be adjusted to the configuration shown in the Plans.

xx. METHOD OF MEASUREMENT. The quantity of Special Provision (Adjust Side Inlet Catch Basin) to be measured for payment will be the number of units modified in the complete and accepted work.

xx. BASIS OF PAYMENT. The accepted quantity of Special Provision (Adjust Side Inlet Catch Basin) will be paid for at the Contract unit price per each at each designated location. Payment will be full compensation for removing and resetting of existing grate, installing a cast iron riser, and for furnishing all labor, tools, equipment, and incidentals necessary to complete the work.

Excavation and backfill associated with adjusting side inlet catch basin will not be paid for separately, but will be considered incidental to Special Provision (Adjust Side Inlet Catch Basin).

Backfill material for backfilling around adjusted side inlet catch basin shall meet the requirements of Subsection 704.08, unless otherwise directed by the Engineer.

Bituminous concrete pavement will be paid for separately under the appropriate Contract item.

Payment will be made under:

| <u>Pay Item</u> | <u>Pay Unit</u> |
|---|-----------------|
| 900.620 Special Provision (Adjust Side Inlet Catch Basin) | Each |