

SLATE ROOF REPAIRS

****From Shrewsbury BHO 1443(49)**

- xx. DESCRIPTION. This work shall consist of performing spot repair(s) to a slate covered bridge roof at the location(s) indicated in the Plans and as directed by the Engineer.
- xx. MATERIALS. Materials for slate roof repairs, including but not limited to new metal hooks, nails, and copper sheets, shall match and be compatible with existing roof materials.
- xx. GENERAL CONSTRUCTION REQUIREMENTS. Slate roof repair shall be made by conventional methods of removing broken slates and securing new roof slates to the remaining adjoining roof slates that are to remain. The materials mentioned above shall be the primary materials used to affect repair. Asphalt roof cement shall not be employed as a primary repair material.
- xx. METHOD OF MEASUREMENT. The quantity of Special Provision (Slate Roof Repairs) to be measured for payment will be the number of each damaged roof location repaired in the complete and accepted work. The work at each damaged roof location shall address replacement of up to three (3) slate shingles.
- xx. BASIS OF PAYMENT. The accepted quantity of Special Provision (Slate Roof Repairs) will be paid for at the Contract unit price per each. Payment will be full compensation for furnishing, handling, transporting, and placing the materials specified, for removing and disposing of existing roofing materials as required by the work, and for furnishing all labor, tools, equipment, and incidentals necessary to complete the work.

Payment will be made under:

<u>Unit</u>	<u>Pay Item</u>	<u>Pay</u>
	900.620 Special Provision (Slate Roof Repairs)	Each