

CRUSHED STONE, ¾"

****From Lunenburg NH CULV(27)**

- xx. DESCRIPTION. This work shall consist of furnishing and placing crushed stone, ¾" underneath the mat foundation and wingwall footings to a depth defined on the plans.
- xx. MATERIALS. Crushed Stone, ¾" shall meet the gradation requirements of Table 704.02B.
- xx. PLACING. Crushed Stone, ¾" shall be placed underneath the mat foundation and wingwall footings to the limits shown on the plans. Geotextile shall be used to separate the crushed stone from the native material.
- xx. METHOD OF MEASUREMENT. The quantity of Special Provision (Crushed Stone, ¾") to be measured for payment will be the number of cubic yards installed in the completed and accepted work, measured within the limits shown on the Plans or as directed by the Engineer.
- xx. BASIS OF PAYMENT. The accepted quantity of Special Provision (Crushed Stone, ¾") will be paid for at the Contract unit price per cubic yard. Payment will be full compensation for furnishing, transporting, and placing the material specified and for furnishing all labor, tools, equipment, and incidentals necessary to complete the work.

Payment will be made under:

<u>Pay Item</u>	<u>Pay Unit</u>
900.608 Special Provision (Crushed Stone, ¾")(FPQ)	Cubic Yard