

LINE DRILLING

****From Brandon NH 019-3(495)**

- xx. DESCRIPTION. This work shall consist of line drilling solid rock subgrade at the locations indicated in the Plans and as directed by the Engineer.

The work under this Section shall be performed in accordance with these provisions, the Plans, and Section 205 of the Standard Specifications.

- xx. CONSTRUCTION REQUIREMENTS. Line drilling holes shall be no more than 75 mm (3 inches) in diameter and shall not exceed 0.50 meters (1.5 feet) in spacing centerline to centerline. These holes shall be drilled prior to production shattering holes and shall not be charged with explosives.

- xx. METHOD OF MEASUREMENT. The quantity of Special Provision (Line Drilling) to be measured for payment will be the number of meters (linear feet) of drill holes drilled in the complete and accepted work. Measurement will be made from the top of the hole to the bottom of the hole at each location.

- xx. BASIS OF PAYMENT. The accepted quantity of Special Provision (Line Drilling) will be paid for at the Contract unit price per meter (linear foot). Payment will be full compensation for performing the work specified and for furnishing all labor, tools, equipment, and incidentals necessary to complete the work.

Payment for clearing and grubbing and for excavation will be made under the appropriate Contract items.

Payment will be made under:

<u>Pay Item</u>	<u>Pay Unit</u>
900.640 Special Provision (Line Drilling)	Meter (Linear Foot)