



CON/SPAN O-SERIES LOAD RATING

SHOP DRAWING REVIEW

REVIEWED AS REQUIRED BY THE CONSTRUCTION CONTRACT DOCUMENTS AND APPROVED, BUT ONLY FOR CONFORMANCE TO THE DESIGN CONCEPT OF THE WORK, AND SUBJECT TO FURTHER LIMITATIONS AND REQUIREMENTS CONTAINED IN THE CONSTRUCTION CONTRACT DOCUMENTS.

REJECTED [X] REVISE AND RESUBMIT [] APPROVED AS NOTED

CORRECTIONS OR COMMENTS MADE ON THE SHOP DRAWINGS DURING THIS REVIEW DID NOT RELIEVE CONTRACTOR FROM COMPLIANCE WITH REQUIREMENTS OF THE DRAWINGS AND SPECIFICATIONS. THIS CHECK IS ONLY FOR REVIEW OF GENERAL CONFORMANCE WITH THE DESIGN CONCEPT OF THE PROJECT AND GENERAL COMPLIANCE WITH THE INFORMATION GIVEN IN THE CONTRACT DOCUMENTS. THE CONTRACTOR IS RESPONSIBLE FOR: CONFIRMING AND CORRELATING ALL QUANTITIES AND DIMENSIONS; SELECTING FABRICATION PROCESSES AND TECHNIQUES OF CONSTRUCTION; COORDINATING THEIR WORK WITH THAT OF ALL OTHER TRADES; AND PERFORMING THEIR WORK IN A SAFE AND SATISFACTORY MANNER.

CLD Consulting Engineers
410 Commercial Street
Manchester, NH 03101
603-668-8223

Job Number: 120106
Reviewed by: NDC
Date: 3/29/16

CONTECH PROJECT #488920

US ROUTE 2
BIRDSBORO RD
TOWN OF LUNENBURG
ESSEX COUNTY, VERMONT

Vermont Agency of Transportation

RECEIVED

ON: March 29, 2016

and Checked for

CONFORMANCE

BY: Danny Landry DATE: 04apr16

DATE: March 16, 2016



LRFR LOAD RATING FACTORS							
LOADING LEVELS	TRUCK						
	<i>H-20</i>	<i>HL-93</i>	<i>3S2</i>	<i>6 AXLE</i>	<i>3A STR.</i>	<i>4A STR.</i>	<i>5A SEMI</i>
<i>TONNAGE</i>	20	36	36	66	30	34.5	38
<i>INVENTORY</i>	1.7	4.1					
<i>POSTING</i>							
<i>OPERATING</i>	6.1	4.3	13.3	6.5	9.2	8.2	12.8
<i>COMMENTS:</i>							



LRFR LOAD RATING ANALYSIS

PROJECT NAME: US ROUTE 2 BIRDGE NO. 126 TOWN OF LUNENBURG
CON/SPAN REF: 468920
DATE: 09-Dec-15
BY: KDK

DEFINITIONS

- O.R.F.** = Operating Rating Factor
I.R.F. = Inventory Rating Factor
 f_y = Yield Stress of Steel
 65 ksi (welded wire fabric)
 60 ksi (plain rebar)
 $f_{s(DL)}$ = Dead Load Stress on Steel (from CANDE output)
 $f_{s(LL+I)}$ = Live Load + Impact Stress on Steel (from CANDE output)
 ϕ = Reduction Factor (per AASHTO LRFD 12.5.5)
 0.95 (COMBINED FLEXURE & THRUST)
 0.90 (SHEAR)
 V_c = Nominal Shear Strength (PER AASHTO LRFD 5.8.3.3 for <2'-0" cover,
 per 5.14.5 for > 2'-0" Cover)
 $V_{(DL)}$ = Dead Load Shear Stress (from CANDE output)
 $V_{(LL+I)}$ = Live Load + Impact Shear Stress (from CANDE output)

EQUATIONS USED IN SPREADSHEET*

- Legal Load O.R.F.** = $(f - 1.25DC - 1.50DW) / (1.40L)$
LRFR Design Load O.R.F. = $(f - 1.25DC - 1.50DW) / (1.75L)$
LRFR Design Load I.R.F. = $(f - 1.25DC - 1.50DW) / (1.35L)$

Where: $D = f_{s(DL)} / f_y$ or $V_{(DL)} / V_c$

$L = f_{s(LL+I)} / f_y$ or $V_{(LL+I)} / V_c$

*Factors applied in CANDE

INPUT PARAMETERS

- | | |
|--------------------|----------------------------|
| Span = 20'-0" | f_y (ksi) = 65 |
| Rise = 9'-3 5/8" | f_c (psi) = 5000 |
| Max Cover = 13'-0" | $V_{c>2'}$ (psi) = 212 |
| Min Cover = 1'-0" | $V_{c\leq 2'}$ (psi) = 141 |



PROJECT
468920

SUMMARY SHEET 3S2 (LRFR)

DESCRIPTION OPR COVER <i>Controlling</i>	TOTAL LIVE LOAD TONNAGE	REDUCTION FACTOR ϕ	OPERATING FACTORED LOAD STRESSES		INVENTORY FACTORED LOAD STRESSES		O.R.F.	OPERATING RATING (TONS)	I.R.F.	INVENTORY RATING (TONS)	
			Steel Stress - ksi		Steel Stress - ksi						
			Shear - psi		Shear - psi						
				DL + LL + I	DL ONLY	DL + LL + I	DL ONLY				
3S2 13'-0" pos. moment	36	0.95	41.6	41.1	N/A	N/A	41.3	1486.8	N/A	N/A	
3S2 13'-0" <i>Neg. Moment, (M-)</i>	36	0.95	34.6	32.4	N/A	N/A	13.3	480.3	N/A	N/A	
3S2 13'-0" shear	36	0.90	111.0	110.2	N/A	N/A	100.7	3626.2	N/A	N/A	

The Operating Rating Factor is: **13.3**



PROJECT
468920

SUMMARY SHEET 6 AXLE TRAILER (LRFR)

DESCRIPTION OPR COVER <i>Controlling</i>	TOTAL LIVE LOAD TONNAGE	REDUCTION FACTOR ϕ	OPERATING FACTORED LOAD STRESSES		INVENTORY FACTORED LOAD STRESSES		O.R.F.	OPERATING RATING (TONS)	I.R.F.	INVENTORY RATING (TONS)
			Steel Stress - ksi		Steel Stress - ksi					
			Shear - psi		Shear - psi					
DL + LL + I		DL ONLY	DL + LL + I		DL ONLY					
6 AXLE TRAILER 13'-0" pos. moment	66	0.95	41.8	41.1	N/A	N/A	29.5	1947.0	N/A	N/A
6 AXLE TRAILER 13'-0" <i>Neg. Moment, (M-)</i>	66	0.95	36.9	32.4	N/A	N/A	6.5	430.5	N/A	N/A
6 AXLE TRAILER 13'-0" shear	66	0.90	111.5	110.2	N/A	N/A	62.0	4091.1	N/A	N/A

The Operating Rating Factor is: 6.5



PROJECT
468920

SUMMARY SHEET 3 AXLE STRAIGHT (LRFR)

DESCRIPTION OPR COVER <i>Controlling</i>	TOTAL LIVE LOAD TONNAGE	REDUCTION FACTOR ϕ	OPERATING FACTORED LOAD STRESSES		INVENTORY FACTORED LOAD STRESSES		O.R.F.	OPERATING RATING (TONS)	I.R.F.	INVENTORY RATING (TONS)
			Steel Stress - ksi		Steel Stress - ksi					
			Shear - psi		Shear - psi					
DL + LL + I		DL ONLY	DL + LL + I		DL ONLY					
3 AXLE STRAIGHT 13'-0" pos. moment	30	0.95	41.6	41.1	N/A	N/A	41.3	1239.0	N/A	N/A
3 AXLE STRAIGHT 13'-0" <i>Neg. Moment, (M-)</i>	30	0.95	35.6	32.4	N/A	N/A	9.2	275.2	N/A	N/A
3 AXLE STRAIGHT 13'-0" shear	30	0.90	111.3	110.2	N/A	N/A	73.3	2197.7	N/A	N/A

The Operating Rating Factor is: **9.2**



PROJECT
468920

SUMMARY SHEET 4 AXLE STRAIGHT (LRFR)

DESCRIPTION OPR COVER <i>Controlling</i>	TOTAL LIVE LOAD TONNAGE	REDUCTION FACTOR ϕ	OPERATING FACTORED LOAD STRESSES		INVENTORY FACTORED LOAD STRESSES		O.R.F.	OPERATING RATING (TONS)	I.R.F.	INVENTORY RATING (TONS)
			Steel Stress - ksi		Steel Stress - ksi					
			Shear - psi		Shear - psi					
DL + LL + I		DL ONLY	DL + LL + I		DL ONLY					
4 AXLE STRAIGHT 13'-0" pos. moment	34.5	0.95	41.5	41.1	N/A	N/A	51.6	1781.1	N/A	N/A
4 AXLE STRAIGHT 13'-0" <i>Neg. Moment, (M-)</i>	34.5	0.95	36.0	32.4	N/A	N/A	8.2	281.3	N/A	N/A
4 AXLE STRAIGHT 13'-0" shear	34.5	0.90	111.2	110.2	N/A	N/A	80.6	2780.1	N/A	N/A

The Operating Rating Factor is: **8.2**



PROJECT
468920

SUMMARY SHEET 5 AXLE SEMI (LRFR)

DESCRIPTION OPR COVER <i>Controlling</i>	TOTAL LIVE LOAD TONNAGE	REDUCTION FACTOR ϕ	OPERATING FACTORED LOAD STRESSES		INVENTORY FACTORED LOAD STRESSES		O.R.F.	OPERATING RATING (TONS)	I.R.F.	INVENTORY RATING (TONS)
			Steel Stress - ksi		Steel Stress - ksi					
			Shear - psi		Shear - psi					
DL + LL + I		DL ONLY	DL + LL + I		DL ONLY					
5 AXLE SEMI 13'-0" pos. moment	38	0.95	41.4	41.1	N/A	N/A	68.8	2615.7	N/A	N/A
5 AXLE SEMI 13'-0" <i>Neg. Moment, (M-)</i>	38	0.95	34.7	32.4	N/A	N/A	12.8	484.9	N/A	N/A
5 AXLE SEMI 13'-0" shear	38	0.90	111.0	110.2	N/A	N/A	100.7	3827.6	N/A	N/A

The Operating Rating Factor is: **12.8**

		PROJECT 468920	SUMMARY SHEET H20 (LRFR)							
DESCRIPTION OPR/INV COVER <i>Controlling</i>	TOTAL LIVE LOAD TONNAGE	REDUCTION FACTOR ϕ	OPERATING FACTORED LOAD STRESSES Steel Stress - ksi Shear - psi		INVENTORY FACTORED LOAD STRESSES Steel Stress - ksi Shear - psi		O.R.F.	OPERATING RATING (TONS)	I.R.F.	INVENTORY RATING (TONS)
			DL + LL + I	DL ONLY	DL + LL + I	DL ONLY				
H20 13'-0" 13'-0" pos. moment	20	0.95	42.1	41.1	42.3	41.1	20.7	413.0	17.2	344.2
H20 13'-0" 13'-0" neg. moment	20	0.95	37.2	32.4	38.2	32.4	6.1	122.3	5.1	101.2
H20 13'-0" 13'-0" <i>Shear, (V)</i>	20	0.90	111.9	110.2	112.4	0.0	47.4	948.0	1.7	33.9

The Inventory Rating Factor is: 1.7
The Operating Rating Factor is: 6.1

Please verify this is correct. This value was 110.2 psi last submission.

Why such a substantial difference between Operating and Inventory ratings? Please review.

		PROJECT 468920	SUMMARY SHEET HL93 TRUCK (LRFR)							
DESCRIPTION OPR/INV COVER <i>Controlling</i>	TOTAL LIVE LOAD TONNAGE	REDUCTION FACTOR ϕ	OPERATING FACTORED LOAD STRESSES Steel Stress - ksi Shear - psi		INVENTORY FACTORED LOAD STRESSES Steel Stress - ksi Shear - psi		O.R.F.	OPERATING RATING (TONS)	I.R.F.	INVENTORY RATING (TONS)
			DL + LL + I	DL ONLY	DL + LL + I	DL ONLY				
HL93 TRUCK 13'-0" 13'-0" pos. moment	36	0.95	41.8	41.1	41.9	41.1	29.5	1062.0	25.8	929.3
HL93 TRUCK 13'-0" 13'-0" Neg. Moment, (M-)	36	0.95	39.3	32.4	39.5	32.4	4.3	153.1	4.1	148.8
HL93 TRUCK 13'-0" 13'-0" shear	36	0.90	112.1	110.2	112.6	110.2	42.4	1526.8	33.6	1208.7

The Inventory Rating Factor is:	4.1
The Operating Rating Factor is:	4.3